

1. Product and Company Identification

Product Name: JP-Y311Aci, 1311Yci
Prior Company Name: Hitachi America Ltd. (superceded on 04/01/2021)
Company Name: Hitachi-IESA, LLC. **Phone Number:**
2730 Greenleaf Avenue (866)583-0048
Elk Grove Village, IL 60007
Web site address: <https://www.hitachi-iesa.com/industrial-marking-and-coding>
Emergency Contact: Chemtrec (800)424-9300
Information: Christian Krzykwa (980)500-7144
Intended Use: Printing ink

2. Hazards Identification

Flammable Liquids, Category 2
Serious Eye Damage/Eye Irritation, Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (single exposure), Category 1
Acute Toxicity: Inhalation, Category 5
Skin Corrosion/Irritation, Category 2
Acute Toxicity: Oral, Category 5
Specific Target Organ Toxicity (single exposure), Category 2
Aspiration Toxicity, Category 2

**GHS Signal Word:****Danger****GHS Hazard Phrases:**

H225 - Highly flammable liquid and vapor.
H319 - Causes serious eye irritation.
H302 - Harmful if swallowed.
H332 - Harmful if inhaled.
H315 - Causes skin irritation.
H370 - Causes damage to organs kidney
H335 - May cause respiratory irritation.
H372 - Causes damage to organs through prolonged or repeated exposure.

GHS Precautionary Phrases:

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting// equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P235 - Keep cool.

GHS Response Phrases:

P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+311 - IF exposed: Call a POISON CENTER or doctor/physician.
P309+311 - Call a POISON CENTER or doctor/physician if exposed or you feel unwell.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P321 - Specific treatment see ... on this label.
P331 - Do NOT induce vomiting.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal Phrases:

P403+233 - Store container tightly closed in a cool and well-ventilated place.
P501 - Dispose of contents/container in accordance with local regulations.
P405 - Store locked up.

Potential Health Effects (Acute and Chronic):

Chronic: Chronic inhalation may cause effects similar to those of acute inhalation. Prolonged or repeated skin contact may cause defatting and dermatitis. Animal studies have reported that fetal effects/abnormalities may occur when maternal toxicity is seen. Chronic overexposure to vapors may cause lung damage. Hazards not otherwise classified (HNOC) or not covered by GHS.

Inhalation:

Causes respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. May cause central nervous system effects such as nausea and headache. Neurobehavioural effects of exposure to MEK (200 ppm for 4 hrs) were studied with 137 volunteers. There were no statistically significant effects observed in biochemical, psychomotor, sensorimotor and psychological tests.

Skin Contact:

May be absorbed through the skin in harmful amounts. Repeated or prolonged exposure may cause drying and cracking of the skin. Only one human case of skin sensitization was located. Negative results were obtained in an animal test; MEK did not produce skin sensitization in the mouse ear thickness test.

Eye Contact:

Causes eye irritation. Vapors may cause eye irritation. Animal evidence suggests that MEK is a moderate to severe eye irritant.

Ingestion:

May cause irritation of the digestive tract. Possible aspiration hazard. May cause central nervous system depression. Animal evidence suggests that MEK can be aspirated (inhaled) into the lungs during ingestion or vomiting.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
78-93-3	Methyl ethyl ketone	~50.0 %
108-65-6	Propylene glycol methyl ether acetate	0.0 -10.0 %
108-88-3	Toluene	< 0.1 %
75-01-4	Vinyl chloride	< 0.1 %
100-42-5	Styrene	< 0.1 %

4. First Aid Measures

Emergency and First Aid Procedures:	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
In Case of Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid. If breathed in, move person into fresh air. Consult a physician.
In Case of Skin Contact:	In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse. Wash off with soap and plenty of water. Consult a physician.
In Case of Eye Contact:	In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes. Get medical aid. Flush eyes with water as a precaution.
In Case of Ingestion:	Potential for aspiration if swallowed. Get medical aid immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Do NOT induce vomiting. Rinse mouth with water. Consult a physician.
Signs and Symptoms Of Exposure:	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Note to Physician:	Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt:	> -5.70 C (21.7 F) Method Used: TAG Closed Cup
Explosive Limits:	LEL: 1.8%vol UEL: 11.5%vol
Autoignition Pt:	404.00 C (759.2 F)
Suitable Extinguishing Media:	In case of fire, use carbon dioxide, dry chemical powder or appropriate foam. Water may be ineffective because it will not cool material below its flash point. Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
Fire Fighting Instructions:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Wear self contained breathing apparatus for fire fighting if necessary. Further information.
Flammable Properties and Hazards:	Carbon oxides.
Hazardous Combustion Products:	No data available.

6. Accidental Release Measures

Protective Precautions, Protective Equipment and Emergency Procedures:	Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.
Environmental Precautions:	Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided. Methods and materials for containment and cleaning up: Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).
Steps To Be Taken In Case Material Is Released Or	Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place

Spilled: in suitable container. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation.

7. Handling and Storage

Precautions To Be Taken in Handling: Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, sparks and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.

Precautions To Be Taken in Storing: Keep away from sources of ignition. Store tightly closed in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area. Keep container tightly closed in a cool, dry, and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
78-93-3	Methyl ethyl ketone	PEL: 200 ppm	TLV: 200 ppm STEL: 300 ppm	No data.
108-65-6	Propylene glycol methyl ether acetate	No data.	No data.	No data.
108-88-3	Toluene	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 20 ppm	No data.
75-01-4	Vinyl chloride	PEL: 1 ppm (See 1910.1017) STEL: 5 ppm	TLV: 1 ppm	No data.
100-42-5	Styrene	PEL: 100 ppm STEL: 600 ppm/(5min/3hr) CEIL: 200 ppm	TLV: 20 ppm STEL: 40 ppm	No data.

Personal Protective Equipment Symbols:



Respiratory Equipment (Specify Type):

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Eye Protection:

Wear chemical splash goggles. Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure. Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Full contact:

Material: butyl-rubber. Minimum layer thickness: 0.3 mm Break through time: > 480 min.
Material: Nitrile rubber. Minimum layer thickness: 0.4 mm. Minimum layer thickness: 0.4 mm Break through time: 480 min.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Other Protective Clothing:	Wear appropriate protective clothing to prevent skin exposure. Impervious clothing. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering Controls (Ventilation etc.):	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ventilation fans and other electrical service must be non-sparking and have an explosion-proof design.
Work/Hygienic/Maintenance Practices:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Environmental Exposure Controls:	Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	yellow. solvent odor.
pH:	No data.
Melting Point:	-87.00 C (-124.6 F)
Boiling Point:	80.00 C (176.0 F) - 146.00 C (294.8 F)
Flash Pt:	> -5.70 C (21.7 F) Method Used: TAG Closed Cup
Evaporation Rate:	No data.
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: 1.8%vol UEL: 11.5%vol
Vapor Pressure (vs. Air or mm Hg):	10.5 kPa at 20.0 C (68.0 F)
	No data.
Vapor Density (vs. Air = 1):	2.41(air=1)
Specific Gravity (Water = 1):	.911 at 25.0 C (77.0 F)
Density:	.805 G/CM3
Solubility in Water:	29g/100mL
Saturated Vapor Concentration:	No data.
Octanol/Water Partition Coefficient:	No data.
Autoignition Pt:	404.00 C (759.2 F)
Decomposition Temperature:	No data.
Viscosity:	No data.
Explosive Properties:	No data available.

Oxidizing Properties: No data available.**Information with regard to primary physical hazard:**

10. Stability and Reactivity

Stability: Unstable [] Stable [X]**Conditions To Avoid -** Ignition sources. Excess heat. Heat, flames and sparks.**Instability:****Incompatibility - Materials To Avoid:** Oxidizing agents. Strong oxidizing agents, Strong acids, 2-propanol, Strong oxidizing agents.**Hazardous Decomposition or Byproducts:** Carbon monoxide, Carbon dioxide, Other decomposition products: No data available. In the event of fire: see section 5.**Possibility of Hazardous Reactions:** Will occur [] Will not occur [X]**Conditions To Avoid -** No data available.**Hazardous Reactions:**

11. Toxicological Information

Toxicological Information: Germ cell mutagenicity: No data available.
Reproductive toxicity.
CAS# 78-93-3:
1. Acute toxicity, LD50, Oral, Rat, 2737. MG/KG.
Result:
Lungs, Thorax, or Respiration: Other changes.
Liver: Fatty liver degeneration.
Blood: Other changes.
- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 19,699, 1971

2. Acute toxicity, LC50, Inhalation, Rat, 23500. MG/M3, 8 H.
Result:
Behavioral: Coma.
Lungs, Thorax, or Respiration: Dyspnea.
Gastrointestinal: Nausea or vomiting.
- American Industrial Hygiene Association Journal., AIHA, 475 Wolf Ledges Pkwy., Akron, OH 44311, Vol/p/yr: 20,364, 1959

3. Acute toxicity, LD50, Intraperitoneal, Rat, 607.0 MG/KG.
Result:
Behavioral: Changes in psychophysiological tests.
- Environmental Research., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 40,411, 1986

4. Acute toxicity, LD50, Oral, Mouse, 4050. MG/KG.
Result:
Behavioral: Sleep.
Behavioral: Headache.
Gastrointestinal: Nausea or vomiting.
- Toxicology Letters., Elsevier Science Pub. B.V., POB 211, 1000 AE, Amsterdam 1000 AE Netherlands, Vol/p/yr: 30,13, 1986

5. Acute toxicity, LC50, Inhalation, Mouse, 32.00 GM/M3, 4 H.

Result:

Gastrointestinal: Alteration in gastric secretion.

Gastrointestinal:Other changes.

- Current Toxicology, Nova Science Publishers, Inc., 6080 Jericho Turnpike, Suite 207, Commack, NY 11725, Vol/p/yr: 1,47, 1993

6. Acute toxicity, LD50, Intraperitoneal, Mouse, 616.0 MG/KG.

Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Ataxia.

Behavioral: Antipsychotic.

- Shell Chemical Company. Unpublished Report., Vol/p/yr: -,6, 1961

7. Acute toxicity, LD50, Skin, Species: Rabbit, 6480. MG/KG.

Result:

Behavioral: Hallucinations, distorted perceptions.

Endocrine:Effect on menstrual cycle.

- Shell Chemical Company., Vol/p/yr: MSDS-5390-,

8. Acute toxicity, LC50, Inhalation, Species: unspecified., 38.00 GM/M3.

Result:

Lungs, Thorax, or Respiration:Other changes.

- Gigiena i Sanitariya, Mezhdunarodnaya Kniga, ul. B. Yakimanka, 39, 113095, Moscow 113095 Russia, Vol/p/yr: 51(5),61, 1986

9. Acute toxicity, LC50, Inhalation, Mouse, 32.00 mg/m3.

Result:

Liver: Fatty liver degeneration.

10. Acute toxicity, LD50, Intraperitoneal, Species: Guinea pig, 2.000 gm/kg.

Result:

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria.

Liver: Tumors.

Blood: Lymphomas including Hodgkin's disease.

Irritation or Corrosion:

Skin corrosion/irritation. Provide adequate ventilation.

No skin irritation . Serious eye damage/eye irritation:

Sensitization:

Maximisation Test.

Carcinogenicity/Other Information:

CAS# 78-93-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65. IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
78-93-3	Methyl ethyl ketone	n.a.	n.a.	n.a.	n.a.
108-65-6	Propylene glycol methyl ether acetate	n.a.	n.a.	n.a.	n.a.
108-88-3	Toluene	n.a.	3	A4	n.a.
75-01-4	Vinyl chloride	Known	1	A1	Yes

100-42-5 Styrene

Possible 2B A4 n.a.

Revision: 04/25/2022
Supersedes Revision: 08/09/2018

12. Ecological Information

General Ecological Information:	Environmental: Substance evaporates in water with T1/2= 3D (rivers) to 12D (lakes). Substance is not expected to bioconcentrate in marine life. Physical: Substance photodegrades in air with T1/2 = 2.3 days. Oxidizes rapidly by photo-chemical reactions in air. Readily biodegradable meeting the 10 day window criterion. Not expected to bioaccumulate significantly.
Results of PBT and vPvB assessment:	PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.
Persistence and Degradability:	Biodegradability: Biotic/Aerobic - Exposure time 8, Result: 100 % - Readily biodegradable. Biochemical Oxygen Demand (BOD) 0.
Other adverse effects:	Chemical Oxygen Demand (COD): An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

13. Disposal Considerations

Waste Disposal Method:	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. RCRA P-Series: None listed. RCRA U-Series: CAS# 78-93-3: waste number U159 (Ignitable waste, Toxic waste). Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contaminated packaging:
-------------------------------	--

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name:	Printing ink.		
DOT Hazard Class:	3	FLAMMABLE LIQUID	
UN/NA Number:	UN1210	Packing Group:	II



LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:	Printing ink. Methyl ethyl ketone.		
UN Number:	UN1210	Packing Group:	II
Hazard Class:	3 - FLAMMABLE LIQUID	TDG Classification:	

LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name:	Printing ink.		
UN Number:	UN1210	Packing Group:	II
Hazard Class:	3 - FLAMMABLE LIQUID		

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Printing ink.
UN Number: UN1210 **Packing Group:** II
Hazard Class: 3 - FLAMMABLE LIQUID

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Printing ink.
UN Number: UN1210 **Packing Group:** II
Hazard Class: 3 - FLAMMABLE LIQUID

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
78-93-3	Methyl ethyl ketone	No	Yes NA	No
108-65-6	Propylene glycol methyl ether acetate	No	No	No
108-88-3	Toluene	No	Yes NA	Yes (0.10%)
75-01-4	Vinyl chloride	No	Yes NA	Yes (0.10%)
100-42-5	Styrene	No	Yes NA	Yes (0.10%)

EPA SARA Title III Section 313 Toxic Release Inventory.

This product contains a toxic chemical or chemicals subject to the reporting requirements of EPCRA Section 313 (40 CFR Section 372).

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Explosive	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Acute toxicity (any route of exposure)
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Flammable (gases, aerosols, liquid, or solid)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Skin Corrosion or Irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Oxidizer (liquid, solid or gas)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Serious eye damage or eye irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Self-reactive	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Respiratory or Skin Sensitization
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Pyrophoric (liquid or solid)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Germ cell mutagenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Pyrophoric gas	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Carcinogenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Self-heating	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Reproductive toxicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Organic peroxide	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Specific target organ toxicity (single or repeated exposure)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Corrosive to metal	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Aspiration Hazard
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Gas under pressure (compressed gas)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Simple Asphyxiant
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	In contact with water emits flammable gas	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	(Health) Hazard Not Otherwise Classified (HNOC)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Combustible Dust		
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	(Physical) Hazard Not Otherwise Classified (HNOC)		

California Proposition 65



WARNING

This product can expose you to chemicals including Vinyl chloride and Styrene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
78-93-3	Methyl ethyl ketone	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC: Cat. IIa, Title 8; NC TAP: Yes: NC TAP
108-65-6	Propylene glycol methyl ether acetate	TSCA: Yes - Inventory, 8A PAIR, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; NC TAP: No
108-88-3	Toluene	TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes: RDTox(F); CA TAC, Title 8: TAC: Cat. IIa, Title 8; NC TAP: Yes: NC TAP
75-01-4	Vinyl chloride	TSCA: Yes - Inventory; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC: Cat. IIa, Title 8; NC TAP: Yes: NC TAP
100-42-5	Styrene	TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC: Cat. IIa, Title 8; NC TAP: Yes: NC TAP

CAS #	Hazardous Components (Chemical Name)	International Regulatory Lists
78-93-3	Methyl ethyl ketone	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes - 1193; Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - 2-542; Japan ISHL: No; Israel HSL: No; Germany WHCS: Yes - 150: WGK 1; Switzerland Giftliste 1: Yes - G-2429; Switzerland INNS: No; REACH: Yes - 01-2119457290-43: Full, (P); Rotterdam: No
108-65-6	Propylene glycol methyl ether acetate	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - 5-1508; Japan ISHL: Yes - 5-1518; Israel HSL: No; Germany WHCS: Yes - 5033: WGK 1; Switzerland Giftliste 1: Yes - G-54973; Switzerland INNS: No; REACH: Yes - 01-2119475791-29: Full, (P); Rotterdam: No
108-88-3	Toluene	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes - 1294; Australia ICS: Yes; New Zealand IOC: Yes - HSR001227; Japan ENCS: Yes - 3-60; Japan ISHL: 4-(7)-2694; Israel HSL: No; Germany WHCS: Yes - 194: WGK 2; Switzerland Giftliste 1: Yes - G-2063; Switzerland INNS: No; REACH: Yes - 01-2119471310-51: Full, (P); Rotterdam: No
75-01-4	Vinyl chloride	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - 2-102; Japan ISHL: No; Israel HSL: No; Germany WHCS: Yes - 462: WGK 2; Switzerland Giftliste 1: Yes - G-2100; Switzerland INNS: No; REACH: Yes - 01-2119458772-30: Full, (P), C1, M2; Rotterdam: No
100-42-5	Styrene	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - 9-2603; Japan ISHL: No; Israel HSL: No; Germany WHCS: Yes - 187: WGK 2; Switzerland Giftliste 1: Yes - G-2896; Switzerland INNS: No; REACH: Yes - 01-2119457861-32: Full, (P); Rotterdam: No

Regulatory Information:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information presented in this document. Final determination of suitability of any material is the sole responsibility of the user to follow local, state and federal laws and regulations in regards to handling of hazardous materials. Although certain hazards are described herein, unknown hazards may exist and caution should always be exercised.

Hitachi Contact Information:

Christian Krzykwa
(704) 972-9887.

16. Other Information


Revision Date: 04/25/2022

Previous revision: 08/09/2018

Hazard Rating System:

HEALTH		1
FLAMMABILITY		3
PHYSICAL		0
PPE		B

HMIS:



NFPA:

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer: