

Page: 1

Revision: 03/29/2015

1. Product and Company Identification

Product Code: TH-84u Product Name: TH-84u

Company Name: Hitachi America, Ltd

50 Prospect Ave Tarrytown, NY

Web site address: www.hitachi-america.us/ice/inkjetprinters/

Emergency Contact: Chemtrec (800)424-9300

2. Hazards Identification

Flammable Liquids, Category 2
Acute Toxicity: Oral, Category 5
Acute Toxicity: Skin, Category 5
Acute Toxicity: Inhalation, Category 5
Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Toxic To Reproduction, Category 1B

Specific Target Organ Toxicity (single exposure), Category 1
Specific Target Organ Toxicity (single exposure), Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (repeated exposure), Category 1
Specific Target Organ Toxicity (repeated exposure), Category 2

Aspiration Toxicity, Category 2







GHS Signal Word: Danger

GHS Hazard Phrases: Highly flammable liquid and vapor.

May be harmful if swallowed.

May be harmful if swallowed and enters airways.

May be harmful in contact with skin.

Causes skin irritation.

Causes serious eye irritation. May be harmful if inhaled.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

Causes damage to organs May cause damage to organs.

Causes damage to organs through prolonged or repeated exposure.

May cause damage to organs through prolonged or repeated exposure.

GHS Precaution Phrases: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray.

Wash hands thoroughly after handling.



Page: 2

Revision: 03/29/2015

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

GHS Response Phrases: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin

with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical attention/advice.

Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical attention/advice if you feel unwell. Specific treatment see Section 4 on this label.

Do NOT induce vomiting.

If skin irritation occurs, get medical advice/attention.

If eye irritation persists, get medical advice/attention.

Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal

Store in cool/well-ventilated place.

Phrases:

Store locked up.

Dispose of contents/container listed in 40 CFR Parts 261.

Potential Health Effects (Acute and Chronic):

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Chronic: Chronic inhalation may cause effects similar to those of acute inhalation. Prolonged or repeated skin contact may cause defatting and dermatitis. Animal studies have reported that fetal effects/abnormalities may occur when maternal toxicity is seen.

Chronic overexposure to vapors may cause lung damage.

Ingredient CAS# 67-56-1, Methanol:

Hazards not otherwise classified (HNOC) or not covered by GHS. None.

Ingredient CAS# 67-64-1, Acetone:

Repeated exposure may cause skin dryness or cracking.

Inhalation: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Causes respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. May cause central nervous system effects such as nausea and headache. Neurobehavioural effects of exposure to MEK (200 ppm for 4 hrs) were studied with 137

volunteers. There were no statistically significant effects observed in biochemical,

psychomotor, sensorimotor and psychological tests.

Skin Contact: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

May be absorbed through the skin in harmful amounts. Repeated or prolonged exposure may cause drying and cracking of the skin. Only one human case of skin sensitization was located. Negative results were obtained in an animal test; MEK did not produce skin

sensitization in the mouse ear thickness test.

Eye Contact: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Causes eye irritation. Vapors may cause eye irritation. Animal evidence suggests that

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.



Page: 3

Revision: 03/29/2015

MEK is a moderate to severe eye irritant.

Ingredient CAS# 78-93-3, Methyl ethyl ketone: Ingestion:

> May cause irritation of the digestive tract. Possible aspiration hazard. May cause central nervous system depression. Animal evidence suggests that MEK can be aspirated

(inhaled) into the lungs during ingestion or vomiting.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration	
78-93-3	Methyl ethyl ketone	90.0 -100.0 %	
67-56-1	Methanol	1.0 -3.0 %	
67-64-1	Acetone	1.0 -3.0 %	
111-76-2	Ethanol, 2-Butoxy-	< 1.0 %	

4. First Aid Measures

Emergency and First Aid

Ingredient CAS# 67-56-1, Methanol:

Procedures:

Consult a physician. Show this safety data sheet to the doctor in attendance.

Ingredient CAS# 67-64-1, Acetone:

Move out of dangerous area.

In Case of Inhalation: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical aid.

Ingredient CAS# 67-56-1, Methanol:

If breathed in, move person into fresh air. Consult a physician.

Ingredient CAS# 67-64-1, Acetone:

In Case of Skin Contact: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

In case of contact, flush skin with plenty of water. Remove contaminated clothing and

shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

Ingredient CAS# 67-56-1, Methanol:

Wash off with soap and plenty of water. Consult a physician.

Ingredient CAS# 67-64-1, Acetone:

In Case of Eye Contact: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes.

Get medical aid.

Ingredient CAS# 67-56-1, Methanol:

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Ingredient CAS# 67-64-1, Acetone:

Ingredient CAS# 78-93-3, Methyl ethyl ketone: In Case of Ingestion:

Potential for aspiration if swallowed. Get medical aid immediately. Do not induce

vomiting unless directed to do so by medical personnel. Never give anything by mouth to

an unconscious person. If vomiting occurs naturally, have victim lean forward.

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.



Page: 4

Revision: 03/29/2015

Ingredient CAS# 67-56-1, Methanol:

Do NOT induce vomiting. Rinse mouth with water. Consult a physician.

Ingredient CAS# 67-64-1, Acetone:

Signs and Symptoms Of

Ingredient CAS# 67-56-1, Methanol:

Exposure:

The most important known symptoms and effects are described in the labelling (see

section 2.2) and/or in section 11

Ingredient CAS# 67-64-1, Acetone:

Note to Physician: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: > -6.30 C (20.7 F) Method Used: Closed Cup

Explosive Limits: LEL: UEL:

Autoignition Pt: 505.00 C (941.0 F)

Suitable Extinguishing Media:Ingredient CAS# 78-93-3, Methyl ethyl ketone:

In case of fire, use carbon dioxide, dry chemical powder or appropriate foam. Water may

be ineffective because it will not cool material below its flash point.

Ingredient CAS# 67-56-1, Methanol:

Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Ingredient CAS# 67-64-1, Acetone:

Fire Fighting Instructions: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear. Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in

low or confined areas.

Ingredient CAS# 67-56-1, Methanol:

Wear self contained breathing apparatus for fire fighting if necessary. Further information. Use water spray to cool unopened containers.

Ingredient CAS# 67-64-1, Acetone:

Flammable Properties and

Hazards:

Ingredient CAS# 67-56-1, Methanol:

No data available.

Ingredient CAS# 67-64-1, Acetone:

Carbon oxides.



Page: 5

Revision: 03/29/2015

6. Accidental Release Measures

Protective Precautions,

Ingredient CAS# 67-56-1, Methanol:

Protective Equipment and Emergency Procedures:

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can

accumulate in low areas. For personal protection see section 8.

Ingredient CAS# 67-64-1, Acetone:

Environmental Precautions: Ingredient CAS# 67-56-1, Methanol:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Ingredient CAS# 67-64-1, Acetone:

Discharge into the environment must be avoided.

Steps To Be Taken In Case Material Is Released Or Spilled:

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation.

Ingredient CAS# 67-56-1, Methanol:

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Ingredient CAS# 67-64-1, Acetone:

7. Handling and Storage

Precautions To Be Taken in Handling:

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, sparks and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor.

Ingredient CAS# 67-56-1, Methanol:

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.

Ingredient CAS# 67-64-1, Acetone:

Precautions To Be Taken in Storing:

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area.

Ingredient CAS# 67-56-1, Methanol:

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Recommended

storage temperature: -20 - 8 deg.C.

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.



Page: 6

Revision: 03/29/2015

Ingredient CAS# 67-64-1, Acetone:

8. Exposure Controls/Personal Protection					
CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits	
78-93-3	Methyl ethyl ketone	PEL: 200 ppm	TLV: 200 ppm STEL: 300 ppm		
67-56-1	Methanol	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm		
67-64-1	Acetone	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm		
111-76-2	Ethanol, 2-Butoxy-	PEL: 50 ppm	TLV: 20 ppm		

Respiratory Equipment

(Specify Type):

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Ingredient CAS# 67-56-1, Methanol:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Ingredient CAS# 67-64-1, Acetone:

Eye Protection: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Wear chemical splash goggles.

Ingredient CAS# 67-56-1, Methanol:

Face shield and safety glasses. Use equipment for eye protection tested and approved

under appropriate government standards such as NIOSH (US) or EN 166(EU).

Ingredient CAS# 67-64-1, Acetone:

Protective Gloves: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Wear appropriate protective gloves to prevent skin exposure.

Ingredient CAS# 67-56-1, Methanol:

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good

laboratory practices. Wash and dry hands.

Ingredient CAS# 67-64-1, Acetone:

Other Protective Clothing: Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Wear appropriate protective clothing to prevent skin exposure.

Ingredient CAS# 67-56-1, Methanol:

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.



Page: 7

Revision: 03/29/2015

Complete suit protecting against chemicals. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Ingredient CAS# 67-64-1, Acetone:

Impervious clothing.

Engineering Controls

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

(Ventilation etc.): Facilities storing or utilizing this material should be equipped with an eyewash facility and

a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ventilation fans and other electrical service must be non-sparking and have an explosion-proof design.

Work/Hygienic/Maintenance

Ingredient CAS# 67-56-1, Methanol:

Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Ingredient CAS# 67-64-1, Acetone:

Environmental Exposure

Ingredient CAS# 67-56-1, Methanol:

Controls:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Ingredient CAS# 67-64-1, Acetone:

Discharge into the environment must be avoided.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Clear.

solvent odor.

 Melting Point:
 -94.00 C (-137.2 F) - 137.00 C (278.6 F)

 Boiling Point:
 56.00 C (132.8 F) - 65.00 C (149.0 F)

Autoignition Pt: 505.00 C (941.0 F)

Flash Pt: > -6.30 C (20.7 F) Method Used: Closed Cup

Explosive Limits: LEL: UEL:

Specific Gravity (Water = 1):

Density: 0.8044 G/CM3

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1):

Evaporation Rate: Solubility in Water: Percent Volatile:



Page: 8

Revision: 03/29/2015

10. Stability and Reactivity

Reactivity: Ingredient CAS# 67-56-1, Methanol:

No data available.

Ingredient CAS# 67-64-1, Acetone:

Stability: Unstable [] Stable [X]

Conditions To Avoid - Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Instability: ignition sources, Excess heat, confined spaces,

Ingredient CAS# 67-56-1, Methanol:

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Ingredient CAS# 67-64-1, Acetone:

Incompatibility - Materials To Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Avoid: Strong oxidizing agents, Strong acids, 2-propanol,

Ingredient CAS# 67-56-1, Methanol:

acids, Bases, Oxidizing agents, Alkali metals,

Ingredient CAS# 67-64-1, Acetone:

Strong reducing agents.

Hazardous Decomposition Or Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Byproducts: Carbon monoxide, Carbon dioxide, Peroxides,

Ingredient CAS# 67-56-1, Methanol:

Other decomposition products: No data available. In the event of fire: see section 5.

Ingredient CAS# 67-64-1, Acetone:

Possibility of Hazardous

Reactions:

Will occur [] Will not occur [X]

Conditions To Avoid - Ingredient CAS# 67-56-1, Methanol:

Hazardous Reactions: No data available.

Ingredient CAS# 67-64-1, Acetone:

Vapors may form explosive mixture with air.



Page: 9

Revision: 03/29/2015

11. Toxicological Information

Toxicological Information: Ingredient CAS# 67-56-1, Methanol:

Germ cell mutagenicity: No data available.

Reproductive toxicity. Aspiration hazard: Ingredient CAS# 67-64-1, Acetone:

Irritation or Corrosion: Ingredient CAS# 67-56-1, Methanol:

Skin corrosion/irritation. No data available. Serious eye damage/eye irritation: Ingredient

CAS# 67-64-1, Acetone: Provide adequate ventilation.

Result: Mild eye irritation -24. Eyes - rabbit -

Result: Eye irritation - 24 h.

Sensitization: Ingredient CAS# 67-56-1, Methanol:

No data available.

Ingredient CAS# 67-64-1, Acetone:

Guinea pig 88%, 4

Result: Does not cause skin sensitisation.

Chronic Toxicological

Effects:

Ingredient CAS# 67-56-1, Methanol:

Specific target organ toxicity - single exposure: No data available. Specific target organ toxicity - repeated exposure: No data available.

Ingredient CAS# 67-64-1, Acetone: May cause drowsiness or dizziness.

Carcinogenicity/Other

Information:

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

CAS# 78-93-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Ingredient CAS# 67-56-1, Methanol:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

Ingredient CAS# 67-64-1, Acetone:

This product is or contains a component that is not classifiable as to its carcinogenicity

based on its IARC, ACGIH, NTP, or EPA classification.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
78-93-3	Methyl ethyl ketone	n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol	n.a.	n.a.	n.a.	n.a.
67-64-1	Acetone	n.a.	n.a.	A4	n.a.
111-76-2	Ethanol, 2-Butoxy-	n.a.	3	A3	n.a.



Page: 10

Revision: 03/29/2015

12. Ecological Information

General Ecological

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Information: Environmental: Substance evaporates in water with T1/2= 3D (rivers) to 12D (lakes).

Substance is not expected to bioconcentrate in marine life. Physical: Substance

photodegrades in air with T1/2 = 2.3 days. Oxidizes rapidly by photo-chemical reactions in air. Readily biodegradable meeting the 10 day window criterion. Not expected to

bioaccumulate significantly. Other: No information available.

Results of PBT and vPvB

Ingredient CAS# 67-56-1, Methanol:

assessment:

PBT/vPvB assessment not available as chemical safety assessment not required/not

conducted.

Ingredient CAS# 67-64-1, Acetone:

Persistence and Degradability:

Ingredient CAS# 67-56-1, Methanol:

No data available.

Ingredient CAS# 67-64-1, Acetone:

Biodegradability Result: 91 % -Readily biodegradable. - Readily biodegradable. (OECD

Test Guideline 301B

Bioaccumulative Potential: Ingredient CAS# 67-56-1, Methanol:

No data available.

Ingredient CAS# 67-64-1, Acetone:

Does not bioaccumulate.

Mobility in Soil: Ingredient CAS# 67-56-1, Methanol:

No data available.

Ingredient CAS# 67-64-1, Acetone:

13. Disposal Considerations

Waste Disposal Method:

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series:

CAS# 78-93-3: waste number U159 (Ignitable waste, Toxic waste).

Ingredient CAS# 67-56-1, Methanol:

Product.

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable

solutions to a licensed disposal company.

Contaminated packaging. Dispose of as unused product.

Ingredient CAS# 67-64-1, Acetone:

Contact a licensed professional waste disposal service to dispose of this material.

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.



Page: 11

Revision: 03/29/2015

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Printing ink related material

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1210 Packing Group: II



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists							
CAS#	Hazardous Components (Chemical Name)		S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)		
78-93-3	Methyl ethyl ketone		No	Yes 5000 LB	No		
67-56-1	Methanol	Methanol		No	Yes 5000 LB	Yes	
67-64-1	Acetone			No	Yes 5000 LB	No	
111-76-2	Ethanol, 2-Butox	y-		No	No	Yes-Cat. N230	
This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard 'Hazard Categories' defined [X] Yes [] No Chronic (delayed) Health Hazard for SARA Title III Sections [X] Yes [] No Fire Hazard 311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard [] Yes [X] No Reactive Hazard							
CAS#	Hazardous Components (Chemical Name) Other US EPA or State Lists						
78-93-3	Methyl ethyl ketone			TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; NC TAP: Yes			
67-56-1	Methanol			TSCA: Yes - Inventory; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; NC TAP: Yes			
67-64-1	Acetone			TSCA: Yes - Inventory, 4 Test; CA PROP.65: No; CA TAC, Title 8: Title 8; NC TAP: No			
111-76-2	Ethanol, 2-Butoxy-			TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; NC TAP: Yes - Cat.			
CAS#	Hazardous Components (Chemical Name) International Regulatory Lists						
78-93-3 67-56-1	Methyl ethyl ketone Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes 1193; Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - (2)-542; Japan ISHL: No; Israel HSL: No; Germany WHCS: Yes - 150; Switzerland Giftliste 1: Yes - G-2429; Switzerland INNS: No; REACH: Yes - (R), (P) Methanol Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes			I IOC: Yes; Japan Israel HSL: No; d Giftliste 1: Yes - H: Yes - (R), (P) No; Mexico INSQ: Yes; Yes; Japan ENCS: Yes			
67-64-1	\ S			 - (2)-201; Japan ISHL: No; Israel HSL: Yes - Cat.; Germany WHCS: Yes - 145; Switzerland Giftliste 1: Yes - G-2063; Switzerland INNS: No; REACH: Yes - (R), (P) Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; 			
Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc. GHS format							



111-76-2

SAFETY DATA SHEET TH-84u

Page: 12

Revision: 03/29/2015

Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - (2)-542; Japan ISHL: No; Israel HSL: No; Germany WHCS: Yes - 6; Switzerland Giftliste 1: Yes - G-1031; Switzerland INNS: No; REACH: Yes - (R), (P)

Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - (2)-2424; Japan ISHL: No; Israel HSL: Yes - Cat.; Germany WHCS: Yes - 47; Switzerland Giftliste 1: Yes - G-1334;

Switzerland INNS: No; REACH: Yes - (R), (P)

16. Other Information

Revision Date: 03/29/2015

Ethanol, 2-Butoxy-

Hazard Rating System:

HEALTH FLAMMABILITY 3 **PHYSICAL** 0 **PPE** В



HMIS:

This Product:

Additional Information About To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Hitachi Contact Information:

Garan Myers

Phone (866) 583-0048

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.