

Page: 1

Revision: 08/27/2019

1. Product and Company Identification

Product Code: TH-413, S4413
Product Name: TH-413ci, S4413ci

Company Name: HHitachi Industrial Equipment & Solutions America, LLC

2730 Greenleaf Avenue Phone Number: Elk Grove Village, IL 60007 (866)583-0048

Web site address: http://https://www.hitachi-iesa.com/industrial-marking-and-coding
Emergency Contact: Chemtrec (800)424-9300

Information: Christian Krzykwa (980)500-7144

2. Hazards Identification

Flammable Liquids, Category 2
Acute Toxicity: Oral, Category 4

Serious Eye Damage/Eye Irritation, Category 2A

Acute Toxicity: Inhalation, Category 4

Carcinogenicity, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

Flammable Liquids, Category 3







GHS Signal Word: Danger

GHS Hazard Phrases: H225 - Highly flammable liquid and vapor.

H315 - Causes skin irritation. H302 - Harmful if swallowed.

H319 - Causes serious eye irritation. H370 - Causes damage to organs kidney

H332 - Harmful if inhaled. Causes respiratory irritation.

H372 - Causes damage to organs central and peripheral nervous systems through

prolonged or repeated exposure.

GHS Precautionary Phrases: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P370+378 - In case of fire, use dry chemical, CO2, water spray, or foam to extinguish.

P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

unwell.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower.



Revision: 08/27/2019

Page: 2

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation persists, get medical advice/attention.

P332+313 - If skin irritation occurs, get medical advice/attention. P307+311 - IF exposed:

Call a POISON CENTER or doctor/physician.

GHS Storage and Disposal

Phrases:

P403+235 - Store in cool/well-ventilated place. P405 - Store locked up. P410 - Protect from

sunlight.

P501 - Dispose of contents/container in accordance with local/regional/national/international

Emergency Overview: regulation.

Potential Health Effects (Acute and Chronic):

Hazards not otherwise classified (HNOC) or not covered by GHS -none. Hazards not otherwise classified (HNOC) or not covered by GHS. Repeated exposure may cause

skin dryness or cracking.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
107-87-9	2-Pentanone	70.0 -80.0 %
64-17-5	Ethyl alcohol	10.0 -20.0 %
108-10-1	Methyl isobutyl ketone	1.0 -10.0 %

4. First Aid Measures

Emergency and First Aid

Procedures:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area.

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician.

In Case of Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Rinse mouth with water. Consult a physician.

Signs and Symptoms Of

Exposure:

The most important known symptoms and effects are described in the labelling (see

section 2.2) and/or in section 11

Indication of any immediate

medical attention and special

treatment needed:

5. Fire Fighting Measures

Flash Pt: > 7.00 C (44.6 F) Method Used: TAG Closed Cup

No data available.

Explosive Limits: LEL: UEL:

Autoignition Pt:

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Fire Fighting Instructions: Wear self contained breathing apparatus for fire fighting if necessary.

Further information.

Carbon oxides.

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.

Multi-region format

Page: 3

Revision: 08/27/2019

6. Accidental Release Measures

Protective Precautions, Protective Equipment and Emergency Procedures: Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

Environmental Precautions: Steps To Be Taken In Case Material Is Released Or Spilled: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. Handling and Storage

Precautions To Be Taken in Handling:

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.

Precautions To Be Taken in Storing:

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Hygroscopic. Protect from sunlight.

Other Precautions:

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated. Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

8. Exposure Controls/Personal Protection				
CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
107-87-9	2-Pentanone	PEL: 200 ppm	TLV: 200 ppm STEL: 150 ppm	
64-17-5	Ethyl alcohol	PEL: 1000 ppm	TLV: 1000 ppm STEL: 1000 ppm	
108-10-1	Methyl isobutyl ketone	PEL: 100 ppm	TLV: 20 ppm STEL: 75 ppm	

Respiratory Equipment (Specify Type):

Respiratory: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Eye Protection:

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Protective Gloves:

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Splash contact:

Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: ? min. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario. Material: butyl-rubber Minimum

layer thickness: 0.3 mm Break through time: 175 min.

Full contact.

Material: Nitrile rubber Minimum layer thickness: 0.4 mm.



Page: 4

Revision: 08/27/2019

Other Protective Clothing: Complete suit protecting against chemicals. Flame retardant antistatic protective

clothing. Impervious clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific

workplace.

Engineering Controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands

(Ventilation etc.): before breaks and at the end of workday.

Work/Hygienic/Maintenance

Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Environmental Exposure

Controls:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: colorless.

Ketone odor.

pH: 0.00

Melting Point: Boiling Point:

Flash Pt: > 7.00 C (44.6 F) Method Used: TAG Closed Cup

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): Specific Gravity (Water = 1):

Solubility in Water:
Octanol/Water Partition

Coefficient:

Autoignition Pt:

Decomposition Temperature:

Viscosity:

10. Stability and Reactivity

Reactivity: No data available.

Stability: Unstable [] Stable [X]

Conditions To Avoid -

Heat, flames and sparks. Heat, Extremes of temperature and direct sunlight.

Instability:

Incompatibility - Materials To Oxidizing agents, Strong bases, Reducing agents, Strong oxidizing agents. Acid

Avoid: anhydrides, Aluminum, Halogenated compounds, Acids.

Hazardous Decomposition or No data available. In the event of fire: see section 5. Other decomposition products:

Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - Vapors may form explosive mixture with air. No data available.

Hazardous Reactions:

Page: 5

Revision: 08/27/2019

11. Toxicological Information

Toxicological Information: Acute toxicity.

Germ cell mutagenicity: No data available.

In vitro mammalian cell gene mutation test: Mouse. lymphoma cells. Result: negative. Reproductive toxicity. Aspiration hazard: Developmental Toxicity. Inhalation. Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Effects on Embryo or

Fetus: Fetal death.

Specific Developmental Abnormalities: Central nervous system. Specific Developmental

Abnormalities: Musculoskeletal system. Specific Developmental Abnormalities:

Cardiovascular (circulatory) system.

Inhalation: Dermal.

Irritation or Corrosion: Skin corrosion/irritation. Skin. Species: Guinea pig. Result: Mild skin irritation (OECD

Test Guideline 404) Serious eye damage/eye irritation: Eyes. Rabbit.

Moderate eye irritation. (OECD Test Guideline 405) Result: Tumorigenic:Tumors at site or application. Mild skin irritation -24 Eyes: No data available. Serious eye damage/eye

irritation no data available. Provide adequate ventilation.

Mild eye irritation Serious eye damage/eye irritation Eyes -rabbit. Eyes - rabbit -

Sensitization: No data available.

Chronic Toxicological

Effects:

Specific target organ toxicity - single exposure: No data available.

toxicity -single exposure: May cause respiratory irritation.

Specific target organ toxicity -single exposure (Globally Harmonized System) Inhalation.

Specific target organ toxicity -repeated exposure: no data available. Specific target organ

Oral. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure:

Carcinogenicity/Other

Information:

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. IARC: 2B - Group 2B:

Possibly carcinogenic to humans (4-Methylpentan-2-one).

This product is or contains a component that is not classifiable as to its carcinogenicity

based on its IARC, ACGIH, NTP, or EPA classification. IARC: 3 -Group 3: Not

classifiable as to its carcinogenicity to humans.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
107-87-9	2-Pentanone	n.a.	n.a.	n.a.	n.a.
64-17-5	Ethyl alcohol	n.a.	1	A4	n.a.
108-10-1	Methyl isobutyl ketone	n.a.	2B	n.a.	n.a.

12. Ecological Information

General Ecological

No data available.

Information:

Results of PBT and vPvB

PBT/vPvB assessment not available as chemical safety assessment not required/not

assessment:

conducted.

Persistence and Biodegradability aerobic -Exposure time 28 d Result: 70 % -Readily biodegradable.

Degradability: Biodegradability: Biotic/Aerobic. No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.

Page: 6

Revision: 08/27/2019

Other adverse effects: No data available.

13. Disposal Considerations

Waste Disposal Method: Product:

> Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste

disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):

Printing ink, [flammable or] Printing ink related material [(including printing ink **DOT Proper Shipping Name:**

thinning or reducing compound), flammable]

3 FLAMMABLE LIQUID **DOT Hazard Class:**

UN/NA Number: 1210 **Packing Group:** Ш



LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:

UN Number: 1210 **Packing Group:** Ш

3 - FLAMMABLE LIQUID **TDG Classification: Hazard Class:**

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
107-87-9	2-Pentanone	No	No	No
64-17-5	Ethyl alcohol	No	No	No
108-10-1	Methyl isobutyl ketone	No	Yes 5000 LB	Yes

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

[] Yes [X] No	Explosive	[X] Yes [] No	lo Acute toxicity (any route of exposure)		
[X] Yes [] No	Flammable (gases, aerosols, liquid, or solid)	[] Yes [X] No	Skin Corrosion or Irritation		
[] Yes [X] No	Oxidizer (liquid, solid or gas)	[X] Yes [] No	Yes [] No Serious eye damage or eye irritation		
[] Yes [X] No	Self-reactive	[] Yes [X] No	Yes [X] No Respiratory or Skin Sensitization		
[] Yes [X] No	Pyrophoric (liquid or solid)	[] Yes [X] No	X] No Germ cell mutagenicity		
[] Yes [X] No	Pyrophoric gas	[X] Yes [] No	[] No Carcinogenicity		
[] Yes [X] No	Self-heating	[] Yes [X] No	o Reproductive toxicity		
[] Yes [X] No	Organic peroxide	[X] Yes [] No	No Specific target organ toxicity (single or repeated exposure)		
[] Yes [X] No	Corrosive to metal	[] Yes [X] No	[X] No Aspiration Hazard		
[] Yes [X] No	Gas under pressure (compressed gas)	[] Yes [X] No	No Simple Asphyxiant		
[] Yes [X] No	In contact with water emits flammable gas	[] Yes [X] No	(] No (Health) Hazard Not Otherwise Classified (HNOC)		
[] Yes [X] No	Combustible Dust				
[] Yes [X] No	(Physical) Hazard Not Otherwise Classified (HNOC)				
CAS#	Hazardous Components (Chemical Name)	Canadian N	IPRI	Canadian Toxic	Canadian DSL
107-87-9	2-Pentanone	No		No	Yes

CAS#	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
107-87-9	2-Pentanone	No	No	Yes
64-17-5	Ethyl alcohol	Yes: Part 5		Yes
108-10-1	Methyl isobutyl ketone	Yes: Part 5	No	Yes
CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists		
107-87-9	2-Pentanone	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8:		
		Title 8; NC TAP:	No	
64-17-5	Ethyl alcohol	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8:		
		Title 8: NC TAP:	No	



Page: 7

Revision: 08/27/2019

TSCA: Yes - Inventory; CA PROP.65: Yes: Canc+RDTox.; CA 108-10-1 Methyl isobutyl ketone

TAC, Title 8: TAC: Cat. IVa, Title 8; NC TAP: Yes: NC TAP

CAS# **Hazardous Components (Chemical Name)** International Regulatory Lists

107-87-9 2-Pentanone Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; Japan ENCS: Yes - 2-542; Japan ISHL: No; Israel HSL: No; Germany WHCS: Yes - 590: WGK 1; Switzerland Giftliste

1: Yes - G-2529; Switzerland INNS: No

64-17-5 Ethyl alcohol Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC:

> Yes; Japan ENCS: Yes - 5-153; Japan ISHL: No; Israel HSL: Yes - Cat.; Germany WHCS: Yes - 96: WGK 1; Switzerland

Giftliste 1: Yes - G-1158; Switzerland INNS: No

108-10-1 Methyl isobutyl ketone Mexico INSQ: Yes - 1245; Australia ICS: Yes; New Zealand

> IOC: Yes; Japan ENCS: Yes - 2-542; Japan ISHL: No; Israel HSL: No; Germany WHCS: Yes - 137: WGK 1; Switzerland

Giftliste 1: Yes - G-2468; Switzerland INNS: No

16. Other Information

Revision Date: 08/27/2019

Hazard Rating System:



HMIS:

Additional Information About

This Product:

Company Policy or

Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information presented in this document. Final determination of suitability of any material is the sole responsibility of the user to follow local, state and federal laws and regulations in regards to handling of hazardous materials. Although certain hazards are described herein, unknown hazards may exist and caution should always be exercised.

Hitachi Contact Information:

Christian Krzykwa (980)500-7144