

Page: 1

Revision: 08/09/2018 Supersedes Revision: 06/01/2016

# 1. Product and Company Identification

Product Code: TH-406
Product Name: TH-406

Company Name: Hitachi Industrial Equipment & Solutions America, LLC

2730 Greenleaf Avenue Phone Number: Elk Grove Village, IL 60007 (866)583-0048

Web site address:https://www.hitachi-iesa.com/industrial-marking-and-codingEmergency Contact:Chemtrec(800)424-9300Information:Christian Krzykwa(980)500-7144

Intended Use: Printing Ink Related Material

#### 2. Hazards Identification

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Acute Toxicity: Oral, Category 5
Acute Toxicity: Inhalation, Category 5
Skin Corrosion/Irritation, Category 2

Specific Target Organ Toxicity (single exposure), Category 1
Specific Target Organ Toxicity (single exposure), Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (repeated exposure), Category 1

**Aspiration Toxicity, Category 2** 







GHS Signal Word: Danger

GHS Hazard Phrases: H225 - Highly flammable liquid and vapor.

H303 - May be harmful if swallowed.

H305 - May be harmful if swallowed and enters airways.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H333 - May be harmful if inhaled.

H336 - May cause drowsiness or dizziness.

H370 - Causes damage to kidneys

H372 - Causes damage to central nervous system through prolonged or repeated

exposure.

**GHS Precaution Phrases:** P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower.

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.

Multi-region format



Page: 2

Revision: 08/09/2018

Supersedes Revision: 06/01/2016

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P307+311 - IF exposed: Call a POISON CENTER or doctor/physician.

P309+311 - Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P314 - Get medical attention/advice if you feel unwell.

P321 - Specific treatment see on this label.

P331 - Do NOT induce vomiting.

P332+313 - If skin irritation occurs, get medical advice/attention. P337+313 - If eye irritation persists, get medical advice/attention. P362 - Take off contaminated clothing and wash before re-use.

**GHS Storage and Disposal** 

Phrases:

P403+235 - Store in cool/well-ventilated place. P405 - Store locked up. P501 -

Dispose of contents/container in accordance with local/regional/national/

international regulation.

**Emergency Overview:** 

**Potential Health Effects** (Acute and Chronic):

Hazards not otherwise classified (HNOC) or not covered by GHS. Hazards not otherwise

classified (HNOC) or not covered by GHS -none.

## 3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
78-93-3	Methyl ethyl ketone	50.0 -80.0 %
64-17-5	Ethyl alcohol	10.0 -40.0 %
67-63-0	Isopropyl alcohol	1.0 -5.0 %

#### 4. First Aid Measures

**Emergency and First Aid** 

**Procedures:** 

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area.

If breathed in, move person into fresh air. If not breathing, give artificial respiration. In Case of Inhalation:

Consult a physician.

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician.

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. In Case of Eye Contact: In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Rinse mouth with water. Consult a physician.

Signs and Symptoms Of

**Exposure:** 

The most important known symptoms and effects are described in the labelling (see

section 2.2) and/or in section 11

Indication of any immediate medical attention and special

No data available.

treatment needed:



Page: 3

Revision: 08/09/2018 Supersedes Revision: 06/01/2016

5. Fire Fighting Measures

Flash Pt: > 1.20 C (34.2 F) Method Used: TAG Closed Cup

Explosive Limits: LEL: UEL:

Autoignition Pt:

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

**Fire Fighting Instructions:** Wear self contained breathing apparatus for fire fighting if necessary.

Further information.

Flammable Properties and

Carbon oxides,

Hazards:

Flash back possible over considerable distance. Container explosion may occur under

fire conditions.

**Hazardous Combustion** 

**Products:** 

#### 6. Accidental Release Measures

Protective Precautions, Protective Equipment and Emergency Procedures: Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can

accumulate in low areas. For personal protection see section 8.

Environmental Precautions:

Steps To Be Taken In Case Material Is Released Or

Spilled:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

.0).

# 7. Handling and Storage

Precautions To Be Taken in

Handling:

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent

the build up of electrostatic charge. For precautions see section 2.

Precautions To Be Taken in

Storing:

Store under inert gas. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent

leakage. Hygroscopic.

Storage class 510) Recommended storage temperature: 2 -8 - 8 deg.C.

Handle and store under inert gas.

Other Precautions: Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

# **8. Exposure Controls/Personal Protection**

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits	
78-93-3	Methyl ethyl ketone	PEL: 200 ppm	TLV: 200 ppm STEL: 300 ppm		
64-17-5	Ethyl alcohol	PEL: 1000 ppm	TLV: 1000 ppm STEL: 1000 ppm		
67-63-0	Isopropyl alcohol	PEL: 400 ppm	TLV: 200 ppm STEL: 400 ppm		



Page: 4

Revision: 08/09/2018 Supersedes Revision: 06/01/2016

Respiratory Equipment (Specify Type):

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator

cartridges as a backup to engineering controls.

If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government

standards such as NIOSH (US) or CEN (EU).

**Eye Protection:** Face shield and safety glasses. Use equipment for eye protection tested and approved

under appropriate government standards such as NIOSH (US) or EN 166(EU).

Protective Gloves: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal

technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good

laboratory practices. Wash and dry hands. Splash contact:

Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 292 min. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed

as offering an approval for any specific use scenario. Full contact.

Material: Nitrile rubber Minimum layer thickness: 0.4 mm.

Other Protective Clothing: Impervious clothing. Flame retardant antistatic protective clothing. The type of protective

equipment must be selected according to the concentration and amount of the

dangerous substance at the specific workplace.

Engineering Controls

(Ventilation etc.):

Work/Hygienic/Maintenance

Practices:

Environmental Exposure

Controls:

Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# 9. Physical and Chemical Properties

Physical States: [ ] Gas [ X ] Liquid [ ] Solid

Appearance and Odor: Clear.

solvent odor.

pH:

**Melting Point:** -89.50 C (-129.1 F) - 129.10 C (264.4 F) **Boiling Point:** 80.00 C (176.0 F) - 82.00 C (179.6 F)

Flash Pt: > 1.20 C (34.2 F) Method Used: TAG Closed Cup

**Evaporation Rate:** 

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1):

Specific Gravity (Water = 1):  $\sim 0.822$ Density:  $\sim 0.804 \text{ g/mL}$ 

Solubility in Water:



Page: 5

Revision: 08/09/2018 Supersedes Revision: 06/01/2016

Octanol/Water Partition

Coefficient:
Autoignition Pt:

**Decomposition Temperature:** 

Viscosity:

10. Stability and Reactivity

Reactivity: No data available.

Stability: Unstable [ ] Stable [ X ]

Conditions To Avoid - Exposure to moisture. Heat, flames and sparks. Extremes of temperature and direct

**Instability:** sunlight.

Incompatibility - Materials To Oxidizing agents, Strong reducing agents, Strong oxidizing agents. Acid anhydrides,

**Avoid:** Aluminum, Halogenated compounds, Acids.

Hazardous Decomposition or No data available. In the event of fire: see section 5. Other decomposition products:

Byproducts:

Possibility of Hazardous

Reactions:

Will occur [ ] Will not occur [ X ]

Conditions To Avoid -

Vapors may form explosive mixture with air. No data available.

Hazardous Reactions:

11. Toxicological Information

**Toxicological Information:** Acute toxicity.

Germ cell mutagenicity: No data available.

Reproductive toxicity. Aspiration hazard: Inhalation: Dermal.

Irritation or Corrosion: Skin corrosion/irritation.

Result: Tumorigenic:Tumors at site or application. No skin irritation. (OECD Test

Guideline 404) Serious eye damage/eye irritation Eyes -Rabbit

Irritating to eyes. No data available. Serious eye damage/eye irritation no data available.

Provide adequate ventilation.

Mild eye irritation Serious eye damage/eye irritation Eyes -rabbit. Serious eye

damage/eye irritation: Eyes - rabbit -

**Sensitization:** No data available.

Chronic Toxicological

Effects:

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity -repeated exposure: no data available. Specific target organ

toxicity -single exposure (Globally Harmonized System) No data available.

Inhalation. Oral. Specific target organ toxicity - repeated exposure:

Carcinogenicity/Other

Information:

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification. IARC: 3 -Group 3: Not classifiable as to its carcinogenicity to

humans.



Page: 6

Revision: 08/09/2018

Supersedes Revision: 06/01/2016

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
78-93-3	Methyl ethyl ketone	n.a.	n.a.	n.a.	n.a.
64-17-5	Ethyl alcohol	n.a.	1	A4	n.a.
67-63-0	Isopropyl alcohol	n.a.	3	A4	n.a.

# 12. Ecological Information

General Ecological

No data available.

Information:

Results of PBT and vPvB

PBT/vPvB assessment not available as chemical safety assessment not required/not

assessment:

conducted.

Persistence and

No data available.

Degradability:

**Bioaccumulative Potential:** No data available. Mobility in Soil: No data available. No data available. Other adverse effects:

# 13. Disposal Considerations

Waste Disposal Method:

Product:

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste

disposal service to dispose of this material.

Contaminated packaging:

## 14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink

thinning or reducing compound), flammable]

FLAMMABLE LIQUID **DOT Hazard Class:** 3

UN1210 **UN/NA Number: Packing Group:** Ш



#### LAND TRANSPORT (Canadian TDG):

**TDG Shipping Name:** 

**UN Number:** 1210 **Packing Group:** Ш

**Hazard Class:** 3 - FLAMMABLE LIQUID **TDG Classification:** 

# 15. Regulatory Information

#### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

<b>CAS #</b> 78-93-3	Hazardous Components (Chemical Name) Methyl ethyl ketone	<b>S. 302 (EHS)</b> No	<b>S. 304 RQ</b> Yes 5000 LB	<b>S. 313 (TRI)</b> No
64-17-5	Ethyl alcohol	No	No	No
67-63-0	Isopropyl alcohol	No	No	Yes

#### This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

[ ] Yes [X] No	Explosive	[X] Yes [ ] No	Acute toxicity (any route of exposure)
[ ] Yes [X] No	Flammable (gases, aerosols, liquid, or solid)	[X] Yes [ ] No	Skin Corrosion or Irritation
[ ] Yes [X] No	Oxidizer (liquid, solid or gas)	[X] Yes [ ] No	Serious eye damage or eye irritation
[ ] Yes [X] No	Self-reactive	[ ] Yes [X] No	Respiratory or Skin Sensitization

Licensed to Hitachi Ink Research and Development: MIRS MSDS, (c) A V Systems, Inc.

Multi-region format



Page: 7

Supersedes Revision: 06/01/2016

Revision: 08/09/2018

		Caporos	00/01/2010
[ ] Yes [X] No	Pyrophoric (liquid or solid)	[ ] Yes [X] No Germ cell mutagenicity	
[ ] Yes [X] No	Pyrophoric gas	[ ] Yes [X] No Carcinogenicity	
[ ] Yes [X] No	Self-heating	[ ] Yes [X] No Reproductive toxicity	
[ ] Yes [X] No	Organic peroxide	[X] Yes [ ] No Specific target organ toxicity	(single or repeated exposure)
[ ] Yes [X] No	Corrosive to metal	[X] Yes [ ] No Aspiration Hazard	
[ ] Yes [X] No	Gas under pressure (compressed gas)	[ ] Yes [X] No Simple Asphyxiant	
[ ] Yes [X] No	In contact with water emits flammable gas	[ ] Yes [X] No (Health) Hazard Not Otherwis	se Classified (HNOC)
[ ] Yes [X] No	Combustible Dust		
[ ] Yes [X] No	(Physical) Hazard Not Otherwise Classified (HNOC)		
CAS#	Hazardous Components (Chemical Name)	Canadian NPRI Canadian Toxic	Canadian DSL
78-93-3	Methyl ethyl ketone	Yes: Part 5 No	Yes
64-17-5	Ethyl alcohol	Yes: Part 5	Yes
67-63-0	Isopropyl alcohol	Yes: Part 5	Yes
CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists	
78-93-3	Methyl ethyl ketone	TSCA: Yes - Inventory; CA PROP.65: TAC: Cat. IIa, Title 8; NC TAP: Yes: N	
64-17-5	Ethyl alcohol	TSCA: Yes - Inventory; CA PROP.65: Title 8; NC TAP: No	No; CA TAC, Title 8:
67-63-0	Isopropyl alcohol	TSCA: Yes - Inventory; CA PROP.65: TAC: Cat. Ilb, Title 8; NC TAP: No	No; CA TAC, Title 8:
CAS#	Hazardous Components (Chemical Name)	International Regulatory Lists	
78-93-3	Methyl ethyl ketone	Mexico INSQ: Yes - 1193; Australia IC IOC: Yes; Japan ENCS: Yes - 2-542; HSL: No; Germany WHCS: Yes - 150: Giftliste 1: Yes - G-2429; Switzerland I - 01-2119457290-43: Full, (P); Rotterd	Japan ISHL: No; Israel WGK 1; Switzerland INNS: No; REACH: Yes
64-17-5	Ethyl alcohol	Mexico INSQ: Yes; Australia ICS: Yes Yes; Japan ENCS: Yes - 5-153; Japa Yes - Cat.; Germany WHCS: Yes - 96 Giftliste 1: Yes - G-1158; Switzerland I - 01-2119457610-43: Full, (P); Rotterd	n ISHL: No; Israel HSL: : WGK 1; Switzerland INNS: No; REACH: Yes
67-63-0	Isopropyl alcohol	Mexico INSQ: Yes - 1219; Australia IC IOC: Yes; Japan ENCS: Yes - 2-207; 2-(8)-319; Israel HSL: Yes - Cat.; Ger WGK 1; Switzerland Giftliste 1: Yes - (INNS: No; REACH: Yes - 01-2119457 Rotterdam: No	Japan ISHL: Yes - many WHCS: Yes - 135: G-1712; Switzerland

#### **Canadian WHMIS Classification:**



reproductive toxicity, etc.)



CLASS B, DIVISION 2: Flammable Liquids CLASS D, DIVISION 2, SUBDIVISION A: Very Toxic Materials (carcinogens,



Page: 8

Revision: 08/09/2018 Supersedes Revision: 06/01/2016

# 16. Other Information

**Revision Date:** 08/09/2018

**Hazard Rating System:** 





HMIS:

Additional Information About This Product:

Company Policy or

Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information presented in this document. Final determination of suitability of any material is the sole responsibility of the user to follow local, state and federal laws and regulations in regards to handling of hazardous materials. Although certain hazards are described herein, unknown hazards may exist and caution should always be exercised.

Hitachi Contact Information: Christian Krzykwa

(980)500-7144