

Page: 1

Revision: 03/03/2022

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 2020/878; US OSHA HCS 2015; and Canadian WHMIS 2015.

Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Code: N940452

Product Name: TH-73u

X Code: X(22,53)0452

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.3 Details of the Supplier of the Safety Data Sheet:

Company Name: Hitachi Industrial Equipment & Solutions America, LLC

2730 Greenleaf Avenue

Elk Grove Village, IL 60007

Information: Christian Krzykwa (980)500-7144

1.4 Emergency telephone number:

Emergency Contact: Chemtrec (800)424-9300

Section 2. Hazards Identification

2.1 Classification of the Substance or Mixture:

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2A

2.2 Label Elements:





GHS Signal Word: Danger

Hazard-determining components of labelling:

2- Butonone

n-Butyl alcohol

GHS Hazard Phrases:

H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation.

GHS Precautionary Phrases:

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313 - If eye irritation persists, get medical advice/attention.

P370+378 - In case of fire, use ... to extinguish.

GHS Storage and Disposal Phrases:



Revision: 03/03/2022

P403+235 - Store in cool/well-ventilated place.

P501 - Dispose of contents/container to ...

UFI:

Adverse Human Health Hazards not otherwise classified (HNOC) or not covered by GHS. Hazards not otherwise 2.3 Effects and Symptoms: classified (HNOC) or not covered by GHS -none.

Section 3. Composition/Information on Ingredients				
CAS#	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	GHS Classification
78-93-3	2- Butonone 01-2119457290-43	75.0 -90.0 %	201-159-0 606-002-00-3	Flam. Liq. 2: H225 Eye Damage 2: H319 STOT (SE) 3: H336 EUH066
67-56-1	Methanol 01-2119392409-28	0.9 -5.0 %	200-659-6 603-001-00-X	Flam. Liq. 2: H225 Acute Tox.(O) 3: H301 Acute Tox.(D) 3: H311 Acute Tox.(I) 3: H331 STOT (SE) 1: H370
64-17-5	Ethyl alcohol 01-2119457610-43	4.765 -14.295 %	200-578-6 603-002-00-5	Flam. Liq. 2: H225
71-36-3	n-Butyl alcohol 01-2119484630-38	1.0 -5.0 %	200-751-6 603-004-00-6	Flam. Liq. 3: H226 Acute Tox.(O) 4: H302 Skin Corr. 2: H315 Eye Damage 1: H318 STOT (SE) 3: H335 H336

Section 4. First Aid Measures

Description of First AidConsult a physician. Show this safety data sheet to the doctor in attendance. Move out of 4.1

dangerous area. Measures:

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

Wash off with soap and plenty of water. Consult a physician. Take victim immediately to In Case of Skin

hospital. Contact:

In Case of Eye Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Flush eyes with water as a precaution. Contact:

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Rinse mouth with water. Consult a physician.

The most important known symptoms and effects are described in the labelling (see 4.2 **Important Symptoms**

section 2.2) and/or in section 11 and Effects, Both

Acute and Delayed:

No data available. 4.3 Indication of any

> immediate medical attention and special treatment needed:



Revision: 03/03/2022

Section 5. Fire Fighting Measures

5.1 Suitable Extinguishing Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Media:

5.2 Flammable Properties Carbon oxides,

and Hazards: Flash back possible over considerable distance. Container explosion may occur under

fire conditions. No data available.

No data available.

Flash Pt: > -2.99 C Method Used: Estimate

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: ~ 340.00 C

5.3 Fire Fighting Wear self contained breathing apparatus for fire fighting if necessary.

Instructions: Further information.

Section 6. Accidental Release Measures

6.1 Protective Precautions, Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure

Protective Equipment

adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

and Emergency

Beware of vapours accumulating to form explosive concentrations. Vapours can

accumulate in low areas. For personal protection see section 8. Wear respiratory

protection.

6.2 Environmental

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Precautions:

Procedures:

6.3 Methods and Material

For Containment and

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see

Cleaning Up:

section 13).

Section 7. Handling and Storage

7.1 Precautions To Be Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof

Taken in Handling: equipment. Keep away from sources of ignition - No smoking. Take measures to prevent

the build up of electrostatic charge. For precautions see section 2.

7.2 Precautions To Be

Taken in Storing:

Store under inert gas. Keep container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent

leakage. Hygroscopic.

Storage class 510) Recommended storage temperature: 2 -8 - 8 deg.C.

Handle and store under inert gas. Hydrolyses readily.

Other Precautions: Apart from the uses mentioned in section 1.2 no other specific uses are stipulated. Apart

from the uses mentioned in section 1.2 no other specific uses are stipulated.

Section 8. Exposure Controls/Personal Protection

8.1 Exposure Parameters:

Exposure i diamotore.				
CAS#	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
78-93-3	2- Butonone	ACGIH TLV	TLV: 200 ppm STEL: 300 ppm	
		Europe	TWA: 600 mg/m3 (200 ppm) STEL: 900 mg/m3 (300 ppm)	
		France VL	TWA: 600 mg/m3 (200 ppm) STEL: 900 mg/m3 (300 ppm)	
		OSHA PELs	PEL: 200 ppm	
		Britain EH40	TWA: 600 mg/m3 (200 ppm) STEL: 899 mg/m3 (300 ppm)	Skin Absorption

HITACHI Inspire the Next

SAFETY DATA SHEET TH-73u

Page: 4

Revision: 03/03/2022

67-56-1 Methanol **ACGIH TLV** TLV: 200 ppm

STEL: 250 ppm

Europe TWA: 260 mg/m3 (200 ppm) Skin Absorption

France VL TWA: 260 mg/m3 (200 ppm)

STEL: 1300 mg/m3 (1000 ppm)

OSHA PFI s PEL: 200 ppm

Britain EH40 TWA: 266 mg/m3 (200 ppm) Skin Absorption

STEL: 333 mg/m3 (250 ppm)

64-17-5 Ethyl alcohol **ACGIH TLV** TLV: 1000 ppm

STEL: 1000 ppm

France VL TWA: 1900 mg/m3 (1000 ppm)

STEL: 9500 mg/m3 (5000 ppm)

OSHA PELs PEL: 1000 ppm

Britain EH40 TWA: 1920 mg/m3 (1000 ppm)

STEL: ()

71-36-3 n-Butyl alcohol **ACGIH TLV** TLV: 20 ppm

> France VL STEL: 150 mg/m3 (50 ppm)

OSHA PELs PEL: 100 ppm

Britain EH40 STEL: 154 mg/m3 (50 ppm) Skin Absorption

8.2 **Exposure Controls:**

8.2.1 Engineering Controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Avoid contact with skin, eyes and clothing. (Ventilation etc.):

Wash hands before breaks and immediately after handling the product.

8.2.2 Personal protection equipment:

Eye Protection: Face shield and safety glasses. Use equipment for eye protection tested and approved

under appropriate government standards such as NIOSH (US) or EN 166(EU).

Protective Gloves: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal

> technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good

laboratory practices. Wash and dry hands. Splash contact:

Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 292 min. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed

as offering an approval for any specific use scenario. Full contact.

Material: Nitrile rubber, Minimum layer thickness: 0.4 mm, Break through time: 480 min.

Other Protective

Impervious clothing. Flame retardant antistatic protective clothing. Complete suit Clothing:

protecting against chemicals. The type of protective equipment must be selected

according to the concentration and amount of the dangerous substance at the specific

workplace.

Respiratory Equipment Where risk assessment shows air-purifying respirators are appropriate use a full-face (Specify Type):

respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator

cartridges as a backup to engineering controls.

If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Respiratory:

Work/Hygienic/Mainten Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. ance Practices:

Revision: 03/03/2022

Page: 5

8.2.3 Environmental Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Exposure Controls:

Exposure Scenarios: No data available.

Section 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: liquid. Color: colorless (Upon aging, clear or colorless fluids may develop a slight

yellow tint which will not affect the product performance).

pH: No data

Melting Point: -97.80 C - -39.00 C

Boiling Point: 64.50 C - 47.6 C (117.72 F)

Flash Pt: > -2.99 C Method Used: Estimate

Evaporation Rate: No data. **Saturated Vapor** No data.

Concentration:

Flammability (solid, gas): No data available.

Explosive Limits: LEL: No data. UEL: No data.

Vapor Pressure (vs. Air or

mm Hg):

No data.

No data.

Vapor Density (vs. Air = 1): No data.

Specific Gravity (Water = 1): No data.

Density: 0.8017 G/ML (6.69 - LB/GA)

Solubility in Water: miscible
Octanol/Water Partition No data.

Coefficient:

Autoignition Pt: ~ 340.00 C **Decomposition** No data.

Temperature:

Viscosity: No data.

Explosive Properties: No data available. **Oxidizing Properties:** No data available.

9.2 Other Information

9.2.1 Information with regard to physical hazard classes

Information with regard to primary physical hazard:

9.2.2 Other safety characteristics

Section 10. Stability and Reactivity

10.1 Reactivity: No data available.

10.2 Stability: Unstable [] Stable [X]

10.3 Conditions To Avoid - Vapors may form explosive mixture with air. No data available.

Hazardous Reactions:

Possibility of Will occur [] Will not occur [X]

Hazardous Reactions:

10.4 Conditions To Avoid - Exposure to moisture. Heat, flames and sparks. Extremes of temperature and direct

Instability: sunlight.

10.5 Incompatibility - Oxidizing agents, Strong reducing agents, Strong oxidizing agents. Acid anhydrides,





Revision: 03/03/2022

Materials To Avoid: Aluminum, Halogenated compounds, Acids. Bases, Alkali metals, Strong acids,

Halogens.

10.6 Hazardous

Decomposition or Byproducts:

No data available. In the event of fire: see section 5. Hazardous decomposition products

formed under fire conditions. -Carbon oxides. Other decomposition products:

Section 11. Toxicological Information

11.1 Information on

Acute toxicity.

Toxicological Effects:

Germ cell mutagenicity. No data available.

Reproductive toxicity. Aspiration hazard: Inhalation: Dermal.

CAS# 78-93-3:

Acute toxicity, LD50, Intraperitoneal, Mouse, 616.0 MG/KG.

Result:

Lungs, Thorax, or Respiration: Sputum.

Biochemical: Metabolism (Intermediary): Other proteins.

Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of

inflammation.

- Shell Chemical Company. Unpublished Report., Vol/p/yr: -,6, 1961

Acute toxicity, LD50, Skin, Species: Rabbit, 6480. MG/KG.

Result:

Lungs, Thorax, or Respiration:Other changes.

Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of

inflammation.

- Shell Chemical Company., Vol/p/yr: MSDS-5390-,

Acute toxicity, LC50, Inhalation, Mouse, 32.00 MG/M3.

Result:

Brain and Coverings: Other degenerative changes.

Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of

inflammation.

Acute toxicity, LD50, Intraperitoneal, Species: Guinea pig, 2.000 GM/KG.

Result:

Immunological Including Allergic: Increase in humoral immune response.

CAS# 67-56-1:

Acute toxicity, LD50, Oral, Rat, 5628. MG/KG.

Result:

Behavioral: Food intake (animal).

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- Gigiena Truda i Professional'nye Zabolevaniya.(Labor Hygiene and Occupational Disease), V/O Mezhdunarodnaya Kniga, Moscow 113095 Russia, Vol/p/yr: 19(11),27,

1975

Acute toxicity, LD50, Intraperitoneal, Rat, 7529. MG/KG.

Result:

Lungs, Thorax, or Respiration: Acute pulmonary edema.

Blood:Changes in leukocyte (WBC) count.

Page: 7



SAFETY DATA SHEET TH-73u

Revision: 03/03/2022

Related to Chronic Data - death.

- EHP, Environmental Health Perspectives., U.S. Government Printing Office, Supt of Documents, Washington, DC 20402, Vol/p/yr: 61,321, 1985

Acute toxicity, LD50, Intravenous, Rat, 2131. MG/KG.

Result:

Kidney, Ureter, Bladder:Other changes in urine composition.

- EHP, Environmental Health Perspectives., U.S. Government Printing Office, Supt of Documents, Washington, DC 20402, Vol/p/yr: 61,321, 1985

Acute toxicity, LD50, Oral, Mouse, 7300. MG/KG.

Result:

Behavioral: Somnolence (general depressed activity).

Lungs, Thorax, or Respiration:Dyspnea.

- Toxicology., Elsevier Scientific Pub. Ireland, Ltd., POB 85, Limerick Ireland, Vol/p/yr: 25,271, 1982

Acute toxicity, LD50, Intraperitoneal, Mouse, 10765. MG/KG.

Result:

Effects on Embryo or Fetus: Fetal death.

Specific Developmental Abnormalities: Other developmental abnormalities.

- EHP, Environmental Health Perspectives., U.S. Government Printing Office, Supt of Documents, Washington, DC 20402, Vol/p/yr: 61,321, 1985

Acute toxicity, LD50, Subcutaneous, Mouse, 9800. MG/KG.

Result:

Effects on Newborn: Growth statistics (e.g., reduced weight gain).

Effects on Newborn: Delayed effects.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 18,185, 1971

Acute toxicity, LD50, Intravenous, Mouse, 4710. MG/KG.

Result:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- EHP, Environmental Health Perspectives., U.S. Government Printing Office, Supt of Documents, Washington, DC 20402, Vol/p/yr: 61,321, 1985

Acute toxicity, LD50, Oral, Species: Monkey., 7.000 GM/KG.

Result:

Behavioral: Muscle weakness.

Behavioral: Ataxia. Behavioral: Coma.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 3,202, 1961

Acute toxicity, LD50, Oral, Species: Rabbit, 14200. MG/KG.

Result:

Specific Developmental Abnormalities: Craniofacial (including nose and tongue).

- FAO Nutrition Meetings Report Series., Vol/p/yr: 48A,105, 1970



Revision: 03/03/2022

Acute toxicity, LD50, Skin, Species: Rabbit, 15800. MG/KG.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Specific Developmental Abnormalities: Musculoskeletal system.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,74, 1974

Acute toxicity, LD50, Intraperitoneal, Species: Rabbit, 1826. MG/KG.

Result:

Specific Developmental Abnormalities: Other developmental abnormalities.

- EHP, Environmental Health Perspectives., U.S. Government Printing Office, Supt of Documents, Washington, DC 20402, Vol/p/yr: 61,321, 1985

Irritation or Corrosion: Skin corrosion/irritation.

Result: Tumorigenic: Tumors at site or application. No skin irritation. (OECD Test

Guideline 404) Serious eye damage/eye irritation Eyes -Rabbit)

Irritating to eyes. No data available. Serious eye damage/eye irritation no data available.

Provide adequate ventilation.

Mild eye irritation Serious eye damage/eye irritation Eyes -rabbit. Serious eye

damage/eye irritation: Eyes - rabbit -

Sensitization:

No data available.

Chronic Toxicological Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Effects:

Specific target organ toxicity -repeated exposure: no data available. No data available. Specific target organ toxicity -single exposure (Globally Harmonized System) Inhalation.

Oral. Specific target organ toxicity - repeated exposure:

Information:

Carcinogenicity/Other IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification. IARC: 3 -Group 3: Not classifiable as to its carcinogenicity to

humans.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
78-93-3	2- Butonone	n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol	n.a.	n.a.	n.a.	n.a.
64-17-5	Ethyl alcohol	n.a.	1	A4	n.a.
71-36-3	n-Butyl alcohol	n.a.	n.a.	n.a.	n.a.



Page: 9

Revision: 03/03/2022

Section 12. Ecological Information

12.1 Toxicity: No data available.12.2 Persistence and No data available.

Degradability:

12.3 Bioaccumulative No data available.

Potential:

12.4 Mobility in Soil: No data available.

12.5 Results of PBT and PBT/vPvB assessment not available as chemical safety assessment not required/not

vPvB assessment: conducted.

12.6 Other adverse effects: No data available.

Section 13. Disposal Considerations

13.1 Waste Disposal Product

Method: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra

care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste

disposal service to dispose of this material.

Contaminated packaging.

Section 14. Transport Information

GHS Classification: Flammable Liquids, Category 2 - Danger! Highly flammable liquid and vapor

Serious Eye Damage/Eye Irritation, Category 2A - Warning! Causes serious eye irritation

14.1 LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink

thinning or reducing compound), flammable]

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1210 II



14.1 LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink

thinning or reducing compound), flammable]

UN Number: 1210 Packing Group: II

Hazard Class: 3 - FLAMMABLE LIQUID TDG Classification:

14.1 LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink

thinning or reducing compound), flammable]

UN Number: 1210 II

Hazard Class: 3 - FLAMMABLE LIQUID





Revision: 03/03/2022

14.3 AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink

thinning or reducing compound), flammable]

UN Number: 1210 Packing Group: ||

Hazard Class: 3 - FLAMMABLE LIQUID

Section 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

•				
CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
78-93-3	2- Butonone	No	Yes NA	No
67-56-1	Methanol	No	Yes NA	Yes
64-17-5	Ethyl alcohol	No	No	No
71-36-3	n-Butyl alcohol	No	Yes NA	Yes
CAS#	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
CAS # 78-93-3	Hazardous Components (Chemical Name) 2- Butonone	Canadian NPRI Yes: Part 5	Canadian Toxic No	Canadian DSL Yes
_	• • •			
78-93-3	2- Butonone	Yes: Part 5		Yes
78-93-3 67-56-1	2- Butonone Methanol	Yes: Part 5 Yes: Part 5		Yes Yes

California Proposition 65



This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

01-2119457610-43: Full, (P)

	www.P65Warnings.ca.gov.	
CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists
78-93-3	2- Butonone	TSCA: Yes - Inventory; CA PROP.65: No
67-56-1	Methanol	TSCA: Yes - Inventory; CA PROP.65: Yes: RDTox.
64-17-5	Ethyl alcohol	TSCA: Yes - Inventory; CA PROP.65: No
71-36-3	n-Butyl alcohol	TSCA: Yes - Inventory; CA PROP.65: No
CAS#	Hazardous Components (Chemical Name)	International Regulatory Lists
78-93-3	2- Butonone	Mexico INSQ: Yes - 1193; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 2-542; Japan ISHL: No; Korea ECL: Yes - KE-24094; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: No; Germany WHCS: Yes - 150: WGK 1; Switzerland Giftliste 1: Yes - G-2429; Switzerland INNS: No; REACH: Yes - 01-2119457290-43: Full, (P)
67-56-1	Methanol	Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 7-322; Japan ISHL: No; Korea ECL: Yes - KE-23193; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: Yes - Cat.; Germany WHCS: Yes - 145: WGK 1; Switzerland Giftliste 1: Yes - G-2063; Switzerland INNS: No; REACH: Yes - 01-2119433307-44: Full, (P)
64-17-5	Ethyl alcohol	Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 5-153; Japan ISHL: No; Korea ECL: Yes - KE-13217; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: Yes - Cat.; Germany WHCS: Yes - 96: WGK 1; Switzerland Giftliste 1: Yes - G-1158; Switzerland INNS: No; REACH: Yes -



Page: 11

Revision: 03/03/2022

71-36-3 n-Butyl alcohol

Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 7-321; Japan ISHL: Yes - 2-(8)-299; Korea ECL: Yes - KE-03867; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: Yes - Cat.; Germany WHCS: Yes - 39: WGK 1; Switzerland Giftliste 1: Yes - G-1321; Switzerland INNS: No; REACH: Yes - 01-2119484630-38: Full, (P)

Section 16. Other Information

Revision Date: 03/03/2022

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information and recommendations contained herein are, to the best of Hitachi's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, HITACHI recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, date and information furnished by Hitachi hereunder are given gratis and Hitachi assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.