



**HITACHI**  
Inspire the Next

# Centrifugal Compressor

Hitachi Centrifugal Compressors





Hitachi a world leader in the manufacturing of heavy industrial equipment, electronics, and consumer product, maintains our strictly controlled quality standards to offer every customer a superior product.

Hitachi has been designing and manufacturing centrifugal compressors since 1910, and has delivered more than 1000 casings to satisfied customers all over the world.

Hitachi, through aggressive R&D, has developed many improvements and many of it' s own innovations in compressor design by use of technology including performance, rotor dynamics, and shaft seal system. We always improve our compressor technology and quality by using a fully computerized design automation system.

Hitachi's advanced centrifugal compressors have excellent reputation for high performance and high reliability and are now working as key components in various plants around world.

Hitachi, having carefully developed its own full design capabilities and having a long supply record can meet customer's requirements for any worldwide project.

<b>CONTENTS</b>	
<b>Compressor Line-up</b>	<b>3—10</b>
Vertically Split Compressors	
Horizontally Split Compressors	
Pipeline Compressors	
Overhang Compressors	
<b>Components</b>	<b>11—16</b>
Casings	
Diaphragms	
Inlet Guide Vane (IGV)	
Rotors	
Bearings	
Seals	
Oil Systems	
Control System	
Seal Gas System	
Magnetic Bearing Control System	
<b>Design</b>	<b>17—18</b>
Design Automation System	
Process Dynamic Simulation	
Nozzle to Nozzle Flow Analysis	
Rotor Dynamics Calculations	
Packaging with 3-D CAD	
<b>Test Facilities</b>	<b>19—20</b>
<b>After-Sales Services</b>	<b>21—22</b>
Retrofit Services and Upgrade Compressor	
Training	
<b>Applications</b>	<b>23—29</b>
Oil & Gas	
Others	
<b>Model Numbers</b>	<b>30</b>



# Compressor Line-up

## Vertically Split Compressors (BCH)

Vertically split casings such as barrel type are applied when the partial pressure of hydrogen exceeds 1380 kPa in accordance with API 617 and/or high-pressure service.


Wall thickness is selected according to pressure. Forged or, in some case, welded construction types are available.

As the vertically split casing is constructed to withstand high pressure, the head covers are bolted or secured with a shear ring.

The bottom section of the bearing support is fixed by bolts and knock pins to provide high rigidity as well as resistance to vibrations. The bearing, however, can still be inspected without the head cover, as with horizontally split casings.


All internal parts can be removed axially without touching the casing, to which the main piping is connected, by simply removing the head cover.

This type is identified by the letter “B”, such as BCH, 2BCH, and BCH/A.



Vertically Split Compressor

Compressor Line-up



BCH802  
Booster Compressor



BCH804  
ATM Compressor



BCH458  
Recycle Compressor



3BCH607  
Propane Compressor



BCH451  
Low Temperature (-165°C) Methane Compressor



# Compressor Line-up

## Horizontally Split Compressors (MCH)


Horizontally split casings, for low and medium pressure, can be supplied in welded steel structures and/or cast steel to meet duty, service temperature and other gas requirements.

Each type feature is sophisticated configuration based on calculations by the FEM analysis.


These casings offer particularly easy maintenance. Nozzles are usually located on the bottom section of the casing, allowing easy removal of the upper section simply by removing the casing nuts. Removal of the upper section provides full access to all internal parts such as the rotor, diaphragms.

Also, bearings can be easily disassembled and inspected by removing only the bearing covers, as it is not necessary to open the casing.


Horizontally split casings are identified by the letter "M", such as MCH, 2 MCH, and 3MCH.



Horizontally Split Compressor




DMCH1406  
Butadiene Compressor



2MCH608  
End Flash Gas Compressor



2MCH806+2MCH607  
Air Compressor



2MCH606  
CO<sub>2</sub> Compressor



3MCH457  
Ethylene Ref. Compressor




# Compressor Line-up

## Pipeline Compressors (PCH)


This type of compressor has one or more open or closed type impellers. The open-piece cast or forged steel casing is designed for pressures up to 100barA and suction and delivery nozzles are located opposite each other to limit thrust loads on the casing. Depending on the driving method used, the casing is either supplied with its own pedestal or flanged to the gearbox. Oil seals are used for shaft end sealing.



PCH601  
Feed Gas Booster Compressor



3-D Image of Skid Type Pipeline Compressor





Pipeline Compressor

## We have developed standardization of pipeline compressors.


In order to optimize the compr. performance in accordance with customer's request, pipeline compressors are standardized into **3 Frames** & **7 Rotors**.

The capacity can be covered from approx. 3,000 to 24,000 m<sup>3</sup>/hr.



PCH802  
Pipeline Booster Compressor

## Arrangement of Gas Turbine and Compressor Module





# Compressor Line-up

## Overhang Compressors


Overhang compressors have single stage with axial flow suction nozzle, which give higher efficiency and wide operating range. The compressor flow is controlled by inlet-guide vane, suction/discharge throttle valve or by-passing. Maintenance of bearing can be done only by opening bearing casing without removing the impeller. The impeller can be easily removed by using special tool supplied by Hitachi.

There are mainly two types of model for the overhang compressors. One is 'POB-GH' type, which is integrally geared type compressor. Another one is 'POB-CH' type, for which speed increasing gear is independently installed. Both types of compressor meet API617 requirements.


Overhang compressors are mainly used for petrochemical industries such as EO/EG plant, propylen plant and etc.




Compressor Casing



POB-CH  
Recycle Compressor




POB-GH  
LLDPE Recycle Compressor



POB-GH Compressor




Rotor of POB-GH Compressor



POB-CH Compressor



POB-CH  
EO/EG Recycle Compressor





# Components

## Casings

Casing is main pressure containing part of compressor. There are two kinds of casing constructions. One is horizontally split type and the other is vertically split type. Based on the pressure and the gas handled, the construction is determined. In terms of material used, there are three types such as cast steel casing, fabricated casing and forged steel casing.




Casing

## Diaphragms

Diaphragms are located in the casing to efficiently convert the dynamic energy of the gas at the impeller outlet to static pressure. Also, return vanes are provided which direct the gas flow to the impeller eye.

Diaphragms are of welded or casting construction, and the return vanes consist of NACA profile wings. In the case of welded construction diaphragm, the return vane wings are precision N/C-machined.

Pressure across the diaphragm differs slightly, but a particularly large differential pressure may occur across the intermediate diaphragms in back-to-back arrangement. In the computer design system, diaphragm deformation calculations are made by FEM with the emphasis places on preventing contract between the diaphragm and the rotor, and the labyrinth and the rotor.




Diaphragm

## Inlet Guide Vane (IGV)

By using IGV, lower starting torque is achieved particularly for refrigeration compressor without raising motor frame size.

IGV also brings benefit of wider turn down range for constant pressure service.



Inlet Guide Vane (IGV)

## Rotors

The rotor consists of shaft, impellers, balancing drum and thrust collar. The shaft is properly heat-treated and the impellers and balancing drum are shrunk-fit to the shaft. Generally, sleeves are placed between the impellers to prevent direct exposure of the shaft to gas.

Two or three dimensional impellers are manufactured by applying a welding or diffusion bonding (welding) (DB) process, machining, or precision forging. The shape of the gas passage, hydrodynamic design points and detailed dimensions of the impellers are accurately determined by computer, based on Hitachi's proven optimum design methods. In the case of welded construction or DB construction, the blades are usually N/C-machined from hubs, welded parts are limited to the shroud and blade. Welded parts are subject to magnetic particle, ultrasonic, radiographic and dye-penetrant inspections, and heat treatment is applied before and after welding and DB.




Five-Axis Machining of a Mixed Flow Impeller




Rotors with Mixed Flow Impellers

## Diffusion Welding Method



## Laser Slot Welding






# Components

## Bearings

### Journal bearings


Tilting pad type bearings are generally used for journal bearings. For every bearing, rotor dynamics calculations are performed, including those for rotor critical speed, stability, and response due to unbalanced mass distribution, with due consideration paid to bearing stiffness and damping caused by oil film.

Tilting pad type bearings are particularly effective against oil whirling and have outstanding stability. Hitachi's pads are constructed to allow for adjustment of the oil clearance.




### Magnetic bearings

Since the active magnetic bearings provide contact-free rotor support, parts and components do not wear. In addition, there is no need for a lubricating system, which improves compressor reliability. With oil-less operation, the bearings suffer no mechanical loss. Without a lubricating system and related components, the utility power required by the compressor is significantly reduced.




### Thrust bearings

The thrust bearings are of the double Kingsbury tilting pad type for equal distribution of the thrust load and minimization of mechanical loss.



### Damper bearings

Damper bearing is used to dampen the rotor and thus stable operation is secured. Due to the oil squeeze film outside of the cage-type spring, the Amplification Factor of critical speed is well suppressed.




Damper bearing assembly

## Seals


These serve to eliminate or minimize the leakage of compressed gas from and the entry of air into the compressor casing. The choice of the seal type is made on the basis of the gas characteristics and operating conditions;

### Dry gas seal



Courtesy of John Crane

### Oil film seal




### Labyrinth seal


- (1) Aluminum seal
- (2) Rub tolerance seal
- (3) Abradable seal



Conventional Aluminum Labyrinth



Rub Tolerance Seal



Abradable Seal



# Components

## Oil Systems

The lube oil system provides forced lubrication to the journal and thrust bearings.

The seal oil system supplies oil at a slightly higher pressure than the compressor's internal gas pressure (reference gas pressure) in case oil film seal and mechanical seal.

Both systems are provided with main and auxiliary pumps, coolers, filters, etc. for continuous operation.

Generally, these systems are designed in accordance with API standards, and all interconnecting piping and valves are compact in size and designed to allow access and operation.


These systems are available as separate systems or as combined system in which the lube oil system supplies some oil to the seal oil system.



Lube Oil Unit

## Control System : HCCS (Hitachi Compressor Control System)

HCCS has adopted HMI as standard. That consists of redundant PLC, anti-surge/performance controller and vibration/bearing temperature monitoring system, which achieves optimized operation and high reliability. Also, the system is very flexible to meet customer's special requirements. By applying the latest brand new technologies, human-friendly system is feasible.



## Seal Gas System


The dry gas seal requires external seal gas, which shall be filtered and shall be free of any contaminants that form residues in order to avoid damage of seal components. The seal gas system supplies the seal gas at a slightly higher pressure than the compressor's internal gas pressure. Generally the seal gas support system is designed to control the seal gas pressure, to measure leakage gas, and to detect abnormal condition of the seal.



Seal Gas Unit

## Magnetic Bearing Control System

In magnetic bearing systems, the compressor shaft is levitated in the air gap by controlling magnetic forces of electromagnets. To regulate the shaft position, the position signals are always feedback to the magnetic forces through the signal processors and power amplifiers. Hitachi has originally developed the controller design and will provide the panel based on this scheme.





# Design

## Design Automation System

### Error Elimination at Every Stage, from Design to Fabrication, Minimizes Operating Problems.

For mission-critical equipment in a plant, such as centrifugal compressors, not even the slightest error in design or manufacture is permissible. Hitachi utilizes the most advanced design and manufacturing technologies available to produce compressors of the highest quality and reliability.

Working from order specifications, the Design Automation System automatically designs and organizes the manufacture of centrifugal compressors, producing everything from drawings to tapes for N/C jobs. This system draws on years of experience as well as the latest data analysis processes and know-how.

Main features of this computer design system:

- Capable of producing complete, error-free designs based on the latest know-how and calculation processes;
- Short design times, ensuring quick delivery;
- Besides producing all drawings and N/C tapes, the system is connected to the overall manufacturing process control system to ensure rapid, high-quality production.



## Process Dynamic Simulation

### Simulation feasible


- Compressor start-up, shut-down
- Parallel Operation of compressors (load-sharing)
- Others

### [Sample of Simulation]

#### Propylene Refrigeration Compressor Start-up simulation




## Nozzle to Nozzle Flow Analysis




## Rotor Dynamics Calculations

The design system outputs data only when the rotor system is completely stable through the entire operating range. Calculations are made not only for torsional analysis and lateral critical speed analysis but also for response due to unbalanced mass distribution, with bearing stiffness and damping, and occasionally aerodynamic excitations, taken into consideration.



## Packaging with 3-D CAD


By adopting 3-dimensional CAD system, packaging of compressor, drivers (ex. motor and gear), seal gas unit, lube unit and relevant auxiliary piping/tubing/wiring are easily planned and designed securing good maintenanceability and easy access.





# Test Facilities


Under ISO9001 certified quality management system, all through the compressor manufacturing process from material receiving and to operational tests and final inspection, there are many inspection and test activities conducted. After assembly work of compressor completed, operational tests such performance test, mechanical running test and/or complete unit test are conducted on the shop test bench. By using a well advanced and sophisticated test facilities, long term reliability is secured. All tests can be carried out in accordance with API and ASME standards.



Complete Unit Test

On-line Test Control Room

## Real Time Access to Hitachi Shop Test



High Speed Motor



BCH804  
Complete Unit Test with 35MW Motor



Satellite Test Bench




# After-Sales Services

With branches in many countries, Hitachi is able to offer after-sales services worldwide.

Our service engineers provide the full set of services needed to support compressor operation.

In addition to conventional maintenance services, Hitachi prides itself on keeping in close contact with customers to ensure the prompt supply of OEM spare parts, repair parts, and retrofit services.



## Retrofit Services and Upgrade Compressor


Hitachi has many experiences of retrofit service and upgrade compressor to centrifugal compressor.

Application of latest technologies, high performance impellers, dry gas seal retrofit, coating system and repairing technologies, can realize reduction of maintenance cost and operating cost. Especially, replacement of compressor internals can be designed to increase the flow rate and for more large demand of process. Hitachi can offer both new high performance compressors and compressor modernizations.

[Before]



[After]



40% Capacity-up with Existing S/T & New Compressors

## Training

Personnel training is offered as a service for our customers.


Conducted in the shop with the actual equipment and skilled instructors on hand, this training allows your staff to acquire/improve their basis knowledge and the skills necessary for compressor operation and maintenance.





# Applications


Oil & Gas






# Applications

## Oil & Gas



PCH802  
Pipeline Booster Compressor



PCH802  
Pipeline Booster Compressor



BCH605  
Natural Gas Treatment Compressor




2BCH357  
Stabilizer Overhead Compressor



BCH804  
Feed Gas Compressor




PCH601  
Feed Gas Booster Compressor





# Applications

Oil & Gas



BCH801  
Recycle Gas Compressor




MCH457+MCH459  
Recycle Compressor



2MCH607  
Wet Gas Compressor




2BCH509+2BCH408/A  
Syn-Gas Compressors



2MCH806+2MCH528  
Process Air Compressors



2MCH606+2BCH306/A  
CO<sub>2</sub> Compressors



Ammonia Plant

Mathanol Plant

LNG Plant

Urea Plant

City Gas Station

Power Station



# Applications

Others



BCH301  
Steam Compressor



BCH302  
Air Compressor



BCH303  
Gas Turbine Fuel Booster Compressor



Seal Water Unit for  
Steam Compressor

# Model Numbers

Hitachi's centrifugal compressors are identified with a 5-block model number, thus:

(1) (2) (3) (4) (5) (6)

**2 BCH 30 6 /A**

- (1) This prefix number indicates the compression group type. No number indicates a single group arrangement with a single outlet and inlet; the number 2 indicates 2-group compression with back-to-back rotor arrangement; and the number 3 indicates a side stream arrangement.
  - (2) The letters indicate the type of casing: MCH represents a horizontally split casing, while BCH indicates a vertically split barrel type casing.
  - (3) The letter 'H' indicates High-quality, High-performance and High-reliability compressors offered by Hitachi.
  - (4) The next set of numbers indicates the nominal diameter of the impeller, in centimeters.
  - (5) The final number indicates the number of stages. Normally, one to nine stages can be incorporated in a single casing.
  - (6) For BCH type compressors, high-pressure models are identified with a suffix: /A, /B, /C, etc.
- (See examples below).

In addition to the above, there are PCH type compressors, intended mainly for pipeline applications. MCH, BCH, and PCH compressors are described on the following pages.


Sample

(1) (2) (3)


3	MCH	100	6	
BCH	45	8		
2	BCH	40	6	/A

(6) For BCH Type only


/A	≥ 10MPa
/B	≥ 20MPa
/C	≥ 35MPa
/D	≥ 50MPa





Unnumbered Straight-through Arrangement



"2" Back-to-Back Arrangement



"3" With Side Stream





# Hitachi Compressor World-Wide Sales Service Network (Main Office)

## U.S.A

### Hitachi Industrial Equipment & Solutions America, LLC

3151 Briarpark Dr.  
Houston TX 77042  
Email: CCS.Info@hitachi-iesa.com

## Brazil & South America

### Hitachi South America Ltda.

Alameda Santos, 745-10º Andar,  
Cjs.101/102 Cerqueira César,  
CEP 01419-001, São Paulo-SP. Brasil Phone:  
<55> (11) 3284-0922  
Fax: <55> (11) 3284-0160

### Hitachi-Mycom Maintenance & Solutions Ltd.

Rua Licatem, 250 Bloco D  
Bairro Parova - Polo Industrial  
Aruja/SP - CEP 07428-280, Brasil  
Phone: <55> (11) 4654-3799

## U.K.

### Hitachi Europe, Ltd.

12th Floor, 125 London Wall  
London EC2Y 5AS, U.K.  
Phone: <44> (20)3872 6195

## Russian Federation

### Hitachi, Ltd.

(Moscow Office)  
Millennium House, 12, Trubnaya Moscow,  
107045, Russian Federation  
Phone: <7> (495) 787-4020  
Fax: <7> (495) 787-4021

## Saudi Arabia

### Hitachi, Ltd.

(Saudi Arabia Branch)  
Al Olaya Center Office No. 102, Makkah  
Al-Mukarramah Street, P.O.Box 79066,  
Al-Khobar 31952, Kingdom of Saudi Arabia  
Phone: <966> (13) 896-1462  
Fax: <966> (13) 893-1033

## U.A.E.

### Hitachi, Ltd.

(Middle East Branch)  
Office No.301, Al Gurg Tower 1,  
Baniyas Road, Deira  
P.O. Box 5561, Dubai, U.A.E.  
Phone: <971> (4) 228-3617  
Fax: <971> (4) 221-1783

## India

### Hitachi India Pvt. Ltd.

(Mumbai Branch Office)  
Unit No.1210, C-wing of One BKC, Plot C-66,  
Bandra Kurla Complex, Bandra (E),  
Mumbai 400 051.  
Phone: <91> (22) 2650-0031  
Fax: <91> (22) 2650-0032

## Singapore

### Hitachi Asia Ltd.

7 Tampines Grande, #08-01 Hitachi Square,  
Singapore 528736  
Phone: <65> 6535-2100  
Fax: <65> 6260-0972

## Malaysia

### Hitachi Asia (Malaysia) Sdn. Bhd.

Suite 17.3, Level 17 Menara IMC  
(Letter Box No. 5)  
No.8 Jalan Sultan Ismail 50250  
Kuala Lumpur  
Phone: <60> (3) 2031-8751  
Fax: <60> (3) 2713-2855

## Indonesia

### PT. Hitachi Asia Indonesia

Menara BCA 38th Floor Suite #3804 & 3805  
Jl. M.H. Thamrin No.1, Jakarta 10310,  
Indonesia  
Phone: <62> (21) 2358-6757  
Fax: <62> (21) 2358-6755

## Thailand

### Hitachi Asia (Thailand) Co., Ltd.

12th Floor, Ramaland Building,  
No.952 Rama IV Road, Suriyawongse,  
Bangrak, Bangkok 10500, Thailand  
Phone: <66> 2632-9292  
Fax: <66> 2632-9299

## Philippines

### Hitachi Asia Ltd.

Unit 8, 11th Floor Zuellig Bldg.,  
Makati Avenue corner Paseo de Roxas,  
Makati City, Philippines 1225  
Phone: <63> (2) 886-9018  
Fax: <63> (2) 887-3794

## Vietnam

### Hitachi Asia (Vietnam) Co., Ltd.

(Ho chi minh city office)  
Room 8-9-10A 4th Floor, The Landmark  
Bldg., 5B Ton Duc Thang Str., Ben Nghe  
Ward, Dist. 1, Ho Chi Minh City, Vietnam  
Phone: <84> (28) 3829-9725  
Fax: <84> (28) 3829-9729

### (Hanoi office)

Room 2310, 23th Floor, Lotte Center Hanoi,  
54 Lieu Giai street, Cong Vi ward,  
Ba Dinh district, Hanoi, Vietnam  
Phone: <84> (24) 3933-3123  
Fax: <84> (24) 3933-3125

## China

### Hitachi (China) Ltd.

(Headquarters)  
18/F., Beijing Fortune Building  
5 Dong San Huan Bei Lu Chao Yang District  
Beijing 100004, China  
Phone: <86> (10) 6590-8111  
Fax: <86> (10) 6590-8110

### (Shanghai Branch)

Ruijin Building, No.205 Maoming Road (S),  
Shanghai 200020, China  
Phone : <86> (21) 6472-1002  
Fax : <86> (21) 6415-8272

### Taiwan Hitachi Asia Pacific Co., Ltd.

3rd Floor, Hung Kuo Building, No.167  
Tun-Hwa North Road, Taipei (105)  
Taiwan  
Phone: <886> (2) 2718-3666, -8777  
Fax: <886> (2) 2718-8180

## Korea

### Hitachi Korea Ltd.

(Head Office)  
10F, Young Poong Bldg., 41,  
Cheonggyecheon-ro,  
Jongno-gu, Seoul 033188, Korea  
Phone: <82> (2) 3210-3590  
Fax: <82> (2) 6322-8598, -8599